









SHUMATI

SHIDATI

0445110107 Injector CRI1-13 Technical File

SPLERT

SAUDATT SHADATT S
1.0445110107 Injector's Introduction
1.1. 0445110107 Injector's Basic Information
1.2. 0445110107 Injector's Common Part Number
1.3.0445110107 Injector's Matching Information
1.4.0445110107 Injector's Parameter
1.5.0445110107 Injector's Specifications and Dimensions 4
1.6. 0445110107 Injector's Quality Control
1.7. 0445110107 Injector's Customized Service
1.8:0445110107 Injector's Packing List and Package Size
1.9.0445110107 Injector's Testing Standard and Certificate
1.10.0445110107 Injector's Warranty Instructions 6
1.10.0445110107 Injector's Warranty Instructions 6 1.11.0445110107 Injector's Manufacturer 7 2.0445110107 Injector Technical Support 8
2.0445110107 Injector Technical Support
2.1.0445110107 Injector's Part Number Location
2.2.0445110107 Injector's Application Scenarios
2 3 0445110107 Injector's Installation 8
2.4. 0445110107 Injector 's Reasons for Not Working Normally92.5. 0445110107 Injector 's Causes of Damage9
2.5. 0445110107 Injector 's Causes of Damage
2.6.0445110107 Injector's Technical Support Obtaining Methods
3.0445110107 Injector's Purchase and Delivery 10
3.2.0445110107 Injector's Main Sales Markets 10
3.1.0445110107 Injector's Purchase Payment Term103.2.0445110107 Injector's Main Sales Markets103.3.0445110107 Injector's Declaration Requirements10
3.4.0445110107 Injector's Shipping Ways 10
3.5.0445110107 Injector's Lead time
3.6.0445110107 Injector's Logistics Time for Destination Out of China's Areas
3.7.0445110107 Injector's Packing
4.0445110107 Injector's Storage Standard12
5. Company Information
5.1. Company Introduction
5.2. Sales-men's Contact Information14
5.2. Sales-men's Contact Information
SANDALL
SANTIAL SATURAL SA

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

and a state of the state of the

. mpr

Tel: +8675523215133 Website : www.shumatt.com

Thus Thus Thus Thus

0445110107 Injector CRI1-13 Technical File

SPARE

SPADE

SHOWER

SALER

SP-ST

States

 $\mathfrak{P}^{\mathbb{N}}$

1.0445110107 Injector's Introduction

-28-⁵⁰⁰ States Street Street Street $\otimes^{0,0}$ 1.1. 0445110107 Injector's Basic Information

and Title of an	China made new high quality diesel injector 0445110107 fuel injector CRI1-13							
SKU 1	G1W20445110107							
SKU 2								
ST ST ST								

1.2. 0445110107 Injector's Common Part Number

(1) Injector's Exchange Information

	change Information	ALTERIA STRUCT SALES TRUCK	STATE - STATE
20 20 3	Injector Part Number	Remanufactured Part Number	2001
the the	0445110107	0 986 435 047	See See
States - States -	0 445 110 108	0 986 435 055	I' de la de
	0 445 110 189		
· · · · · · · · · · · · · · · · · · ·			

(2) Injector's Application Information

Injector Part	MERCEDES-BENZ Car			
Number	Model			
0 445 110 108	611 070 14 87	and and the second	and the and the an	and and the set
0 445 II0 108 M	A 611 070 14 87	0. 0.	0. 0. 0.	
0 445 110 107	611 070 14 87	and all all	a state a state of	and a contra
8410 443 Sho TOA 84	A 611 070 14 87	Str. Str.	Sec. Sec. Sec.	34n - 34n
. The state .	611 070 16 87	Star Star Sta	i sate star	and and
an an	A 611 070 16 87	. Stor. Stor.	aller aller alle	n 94 - 36
0 445 110 189	A 611 070 16 87 06		Day Day 1	Stern Stern
Strates at the set	611 070 14 87	aten sten	Style Style Sty	en stern ste
in in	A 611 070 14 87		n n	
and and a	611 070 16 87 06	the state state	and and a	the state of the s
	611 070 14 87			
0 986 435 047	611 070 14 87 0080	and an and a start	and the second and	and and and and
	A 611 070 14 87 0080	in		
and the second in the second in the second s	A 611 070 14 87	and a start and	The state of the second	ant - antitation
su, su, su	611 070 16 87	20. 20.	- ST - ST	\$4° \$4
and and .	A 611 070 16 87 06	and water and	The The	ant anti-
31° 31° 31	A 611 070 16 87 80	210 - 210	- 11 - 11 - 11 - 11 - 11 - 11 - 11 - 1	- 3°° - 3°°
0 986 435 055	A 611 070 14 87	the Day Day	Day Day	
and all all all all all all all all all al	A 611 070 14 87 80	Store Store	appendance at	1 9 M
	611 070 16 87 0080	and the set	i sti sti	
AND AND ST	A 611 070 16 87 0080	n' state state	AM AM A	the state of the
	611 070 1487			
and and a	en ^{Arten} e Artene Artene	and and a set	· Prins. Prins. ?	ant ^{an} anta ⁿ a

Mob/WhatsApp: +86 13410541523 Email : ruby@shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd

Shenzhen Shumatt Technology Co., Ltd 611 070 1/ 87 80

13 M	011 070 14 87 80	1 di 1	1AA.	S
straw, straw, st	A 611 070 16 87	and a second second	Strange Strange	
~ ~	611 070 16 87 06			
all all all all all	611 070 16 87 80	The state of the	all all at	and all all

(3) Injector's Part Number Common Writing

0445110108, 0445110107, 0445110189, 0986435047, 0986435055, 0 445 110 108, 0 445 110 107, 0445 110 189, 0986 435 047, 0986 435 055, 0445 110108, 0445 110107, 0445 110189, 0 986 435047, 0 986 435055, 0 445110108, 0 445110107, 0 445110189, 0 986435047, 0 986435055, 0445 110 108, 0445 110 107, 0445 110 189, 0986 435 047, 0986 435 055, 0445110 108, 0445110 107, 0445110 189, 0986435 047, 0986435 055, 0445 110108, 0445 110107, 0445 110189, 0986 435047, 0986 435055, A 611 070 14 87 0080, A61107014870080, A 611 070 16 87 80, A611070168780, 611 070 16 87 0080, 61107016870080, 611 070 14 87 0080, 61107014870080, A 611 070 14 87 80, A611070148780, A 611 070 16 87 0080, 611 070 1487, 611 070 14 87, 6110701487, 611 070 16 87 06, 611070168706, 611 070 16 87, 6110701687, A 611 070 14 87, A6110701487, A61107016870080, 611 070 14 87 80, 611070148780, 611 070 16 87 80, 611070168780, A 611 070 16 87A6110701687, A 611 070 16 87 06, A611070168706

brand Series Model Model date (KW) standard power Manufacturer Emission Cylinder	er Source (V)
MERC EDES- BENZ Sprin (T1N) 208 611. OM 04/2000 60 82 PS 60 / / / / / 4	12
MERC EDES- BENZ Sprin (T1N) 211 (CDI) OM 611. 981 981 04/2000 - 05/2006 80 kW 109 PS / / / / / / / 4	12
MERC EDES- BENZ Sprin (T1N) 213 (CDI) OM 611. 981 05/2006 04/2000 95 kW 129 PS 95 kW /	12
MERC EDES- BENZ Sprin (T1N) 216 (CDI) OM 612. 981 04/2000 115 115 kW 156 PS / <td>12</td>	12
MERC EDES- BENZ Sprin (T1N) 311 CDI OM 611. 981 08/2002 80 109 PS / / / / / / 4	12
MERC EDES- BENZ Sprin (T1N)) 313 CDI OM 611. 95 04/2000 95 129 PS / / / / / 4	12

Mob/WhatsApp: +86 13410541523 Email : ruby@shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd

			5110		mum			<u>'gy CO., Lit</u>	J			
MERC EDES- BENZ	Sprin ter [T1N]	313 CDI Sprint er 4x4	OM 611. 981 D LA	08/2002 - 05/2006	95 kW	129 PS	/	/	1	4		12
مربع 1.4.0)445110	107 Injeo	ctor's Pa	arameter	Stern	-Stores	S.630	21. ³¹ . 3	200 - SA	an ala	an an	
Injec	tor Serie	es: 110 S	eries		n. -51 ^{0,200}	STA STATE	SI S	STT SPARATT SP	1200 TT 510	2077 ¹⁷ 5182	10 ⁵⁷⁵ 515	
Mate	ching Ac	erforman cessories e: Electro	e 1	1-13 cic Injector	CT 578-575	ATT STREET	rt Sil ^{ani}	STA STATEST	NETONICE STR	2009.7.5 518.5	51 ⁵¹ 51 ⁵¹ 51 ⁵⁵	
Supp	ort Syst	em Maxiı	num Pr	essure: 13 ntion: MERC		enz enz	STR. STR. STR.	NT SHUDAT SI	UNDALL SH	STONET STRI	58 ^{417 T} 58 ⁴⁵	
1.5.0	يمد 445110	0107 Injec	tor's Sp	pecification	is and I	Dimensio	r ^{rt} ns ^{szelő}	art station st	unite st	MART SPEE	NATT SHE	
Injec	tor Size	Weight:	1*4 cm *	'4 cm = 344	çm³ (L* چې ^{وریت}	W*H=V)	SRUTT	STI SPUDDIT SI	UDATT SP	20 ²⁰¹¹ 5183	2977 51 ⁵¹	
Injec	tor Qua			Brand New cm = 1372	and the second sec	SPLIN	ST STUD	STT SHUDDET ST	unati sa	SPATT SPRI	on ^{rit} st ^g i	
-	udhan i tha ann	e: Diesel ces	ugh, huitean an a	n Rail Inject	or St ^{alen}	ST. SPECIE	570,50	STT STADDITT ST	AND SH	2007 - 5182	51 ⁵⁷ 51 ⁵⁵	
	01	0107 Inje or Testing	ctor's Q	uality Con	rol	ST. SHARE	ST STREET	ST SMART SI	USBATT ST	STATT SIRE	10 ⁵⁷⁷⁵ 51 ⁸⁵	

(1) Injector Testing

All injector spare parts are tested for electrical characteristics, accuracy, high temperature, low temperature, withstand voltage, leakage, durability, and various working conditions.

(2) Injector Assembling

And the quality control of the injector production and installation process, our company strictly follows the standard product installation data and product installation steps to install, such as injector stroke test, injector solenoid valve tightening torque, injector nozzle tightening torque, 54500

SHERE SHERE SHERE

(3) Injector Inspection

and the and the

33^{980 -}

The factory inspection of the injector is undergone full inspection, random inspection, and batch inspection three inspections. Different brands of test benches are used to test the same fuel injector for a total of no less than three times for factory inspection, and the fuel injector installation testing environment are progressed in dust-free workshop.

1.7. 0445110107 Injector's Customized Service

(1) Injector's Customized Service: Meet the customized needs of OEM manufacturers for shell lettering, logo engraving, injector internal packaging, injector external packaging and labels customized, etc.

. 18⁴⁷

Mob/WhatsApp: +86 13410541523 Email:ruby@shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd Tel: +8675523215133 Website : www.shumatt.com $\mathfrak{gl}^{[k]}$



SPUMPT	at I at		pi	5777 5192
SPUDAT	SHO SHOW		ja Santa ja Santa ja Santa ja Santa ja Santa	ant' sili
STURFE	Injector nozzle engraving	Injector house lettering and QR code	Injector box and label	17.5 ⁵ - 38.5

(2) Injector's Customized Service Requirements:

The purchased of customized injector are not less than 10 pieces. Customized injector packages no less than 1000 pieces.

Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file.

A Once the customized fuel injector is sold, it cannot be returned or exchanged if there is no quality problems.

1.8.0445110107 Injector's Packing List and Package Size

(1) Injector Spare Parts List

No.		2.00 ¹	- m ¹ - m ³ - m ¹
Store Store	an an an an	Store Store	58 ⁷⁷ 58
str ^{jon} imáge Str ^{jon} str ^{jon}			an ^u O ian
Name	Fuel Injector	O-Ring	Gasket F 00V C17 503
Description	Fuel injector part number: 0445110107	Ensure to meet the standard of the sealing performance between the injector and the engine	Made of brass, used to ensure the tight fit between the injector cap end and the engine
No.	d 4 d 4	ే5	a 6 a a
A Mage A			STAR IN
Name	Nozzle Protective Cover Cap	Injector House Protective Cover Cap	Solenoid Valve Protective Cap
Description	Protect nozzle holes from being polluted and blocked	Protect oil inlet from being polluted and blocked	Protect the solenoid valve body and terminals from being damaged by external forces
No. 🔗	and and and and	8.07	0° 0°
and		51 ⁻	
and the second	S	the lite lite in	الكمر الكمر الكمر
	VCI Anti-rust Bag	Bubble Bag	Injector Packing Box
Name			Place injector and injector

▲ Minors are forbidden to use the fuel injector assembly, O-ring, gasket, nozzle protective cover, fuel injector house protective cover, solenoid valve protective cover, VCI anti-rust bag, and air bubble bag to avoid personal injury.

• O-ring and gasket are disposable installation accessories, and need to be replaced for re-installation.


A The nozzle protective cover, the injector house protective cover, and the solenoid valve protective

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

cover are recyclable accessories that can be reused.

VCI anti-rust bags and bubble bags are non-degradable materials, please dispose of them properly after using.

▲ The injector and the installation parts should be coated with appropriate sealing oil during installation.



		<u> </u>		
-33	No.	Name	Injector Package Size (cm)	ġ.
	1	Injector Box	28*7*7	
	and the	- The The	the attended the attended attende	

1.9.0445110107 Injector's Testing Standard and Certificate

We can provide the factory quality inspection test report of each injector to ensure that each injector delivered meets the engine performance indicators.

	n. 30	2	<u> </u>	- 1994 - C	all	da e	Sec.	201	201	241	200
TEN	测试报告	4.05.201	9 10:42:09								
H企业:				100	r steine	57 SPLINE	STALLON STALLON	STALES	SAUDE SAUDE	ari Status	57 17
9121 :	18址:			320	- A. 1990	Aller	add the second	- A.S.	- A.S.	A.S. 19	- 43
4 Ξ :	松潤人:			200	100	201	201	201	353	350.	200
en#15:											
5ið	送检单位。				đ	di s	a .	ari Silutai	17. 519.507	ari Stratte	17 ≅1 ⁸³
ł¤:	客户姓名:		-	. 68	TT SPRINT	57 SPAINE	TI SPUTT	10 a. 10 a.	10 a dil	10 a di 1	1
KPRINIE:				200	Sec.	25	- 18 C	1979 - C	200	1997 - C.	- 377
(州名称:)	6 #25										
								_	-	~	
				32.575	STRUMP	TT SPORT	TI SPLER	ari. Shutai	SPURI	Strate	17 31 ⁸³
21A.				133 M	183 M	- A.S.	- A.S.		- 13 ST		a the second
	检测结果	E		58 Y L	200	dian.	200	20.	2001	200	200
-00000 : 01088090 : 000000- 10166		excen contrat									
LEAK TEST: 32		es 20.82-11.6	~		A	- A	SILLER	1	10	19	10
Fade: at WARM: at		0 	-	15	STREET	ST SPORT	er ande	ST STUDI	an anan	ST. SHERE	17 38 ³
Mai: 2013		e	~	40 ⁰⁰⁰⁰		Star .	- Star		53000	all and a second	- 28 ⁰⁰
TL: 364 LL: 160		0 ·····b·····	1						101-1	100 ⁻¹⁰	
VE: 42	4.5±1.8	o	*								
					STREET	57 - 5830F	S. State	an Anta	ST. SHEEL	ST. SWEET	1 ⁵⁷ 1979
				53.205		1	63 ⁹⁷	1	1	11	1
				300	- 93.5	-96-	- 53 Co.	681	- 32.00	- 682.00	- 335.
11 02 02 04 住印前 重注册	desdesdesde8	6915.									
					er Steller	579,500	ST. STATE	state	ST. SANTO	ST. SWITT	5 51
çe. Ş	it ^{yn} si	1,500 S	de an	1.00	100	1.00	- 10 M		- 1.5°	-4.20	

1.10.0445110107 Injector's Warranty Instructions

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

 $\sim 10^{-1}$

(1) . Product Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the injector inspection equipment when the injector is abnormal during use as evidence to feed back to the salesman.

Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting the engine, 4. Engine noise, 5. oil leakage etc.

(2) . Injector Warranty Coverage

 $\mathcal{A}^{(2)}(t)$ Within 15 days after customer receives the 0445110107 injector, if there is a performance failure and المراجعة the product has no appearance damage, customer can choose to replace it or repair it;

If the 0445110107 injector has performance problems during the warranty period (3 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

If the injector house has obvious scratches, it can only be repaired and it will be returned as it is if the product is confirmed to be fault-free.

A Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 months from the date of repairing. 100 STREET, STREET, STREET, STREET,

(3) . Injector Out of Warranty Coverage

The warranty period has expired.

Injector failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, earthquake, and used in abnormal environment.

Customer disassembles or repairs the injector personally resulting in damage to the injector.

Injector damage caused by man-made reasons (throwing, strong magnetic field magnetization, set fire). Injector failure or injector damage caused by non-injector design, technology, manufacturing, quality THE A DEAL A DEAL A DEAL A DEAL A DEAL and other issues.

Injector failure due to system pressure exceeding system approved pressure.

Injector failure caused by system voltage exceeding approved voltage.

Injector failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in the system fuel exceeding the standard requirements.

Injector failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).

Injector failure caused by not following the installation angle specified in the vehicle engine maintenance -stall? -18-50° " States, States, States, States, States, A.S. manual.

Injector failure caused by not following the cleaning requirements specified in the vehicle engine NEEL maintenance manual. OF T

Injector failure caused by failure to replace consumable parts as specified in the vehicle engine maintenance manual. d Da d 1 -

Injector failure caused by not complying with the intake system fit clearance and exhaust system fit clearance requirements specified in the vehicle engine maintenance manual.

Failure to replace the consumable parts and the fitting clearance of the oil inlet system pipeline and the fuel injector connection in accordance with the fuel intake system specified in the vehicle engine maintenance manual.

1.11.0445110107 Injector's Manufacturer

Injector's manufacturer: Shenzhen Shumatt Technology Co., Ltd

Mob/WhatsApp: +86 13410541523 Email:ruby@shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd

3.9⁵⁹⁷ 2.0445110107 Injector Technical Support

2.1.0445110107 Injector's Part Number Location

1) E.g.: The injector part number see as follows




. 1	No.			Nam	e	
ler.	53.00	30	brand	, logo, pa	irt numbe	er, 🕬
	A			series nu	mber	
10	e st Be st	. 6	no	zzle part	number	с. С
Con	Silon.	30.0	20,00	20.00	20.0	- 54.

CALIFORN .

SPATTON

-31^{0,008} 2.2.0445110107 Injector's Application Scenarios

Common rail system is an oil supply method refers to the diesel oil from the fuel tank sucked out by the gear pump through the oil-water separator and the gear pump to diesel fine filter, high-pressure pump, common rail pipe, and fuel injector, all together with the closed-loop fuel supply system composed of sensors and ECU that completely separates the generation of injection pressure and the injection process from each other.





and the	and and	li Ali	Pic Pic	: No. 1	all all the set	anti a	and a and a
No.	Name	No.	Name	No.	Name	No.	Name
-Aller C	Tank	् दुर्जुले	Common Rail Pressure Sensor	9	Engine Crankshaft Sensor	Â	High Pressure Oil Circuit
2	Diesel Filter	6	Common Rail Pipe	10	Camshaft Sensor	B	Low Pressure Oil Circuit
300	High-Pressure Pump	7.0	Injector	31 ²⁰	ECU Electronic Control Unit	19 ⁵³ -28	1997 - 33,1997 - 38
4	Fuel Gear Pump	8	Accelerator Pedal			-144 A	

Pic No. 1

2.3.0445110107 Injector's Installation (1) .0445110107 Injector's Installation Precautions:

A The replacement of the fuel injector must strictly follow the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter and the high-pressure fuel circuit) specified in the vehicle engine maintenance manual,

A Replacement of wearing parts of the fuel system, cleaning requirements for the connection between the fuel system and the injector, the fitting clearance of the fuel injector connection, the installation angle and

tightening torque of the injector, the fitting clearance of the intake system, and the fitting clearance of the exhaust system to ensure the service life of the engine and the normal operation of the injector. When installing the fuel injector on the engine, it is necessary to clean the engine block, cylinder head and other parts connected to the fuel injector, and ensure that there is no dust, carbon deposits, water, rust

 $\sim \phi^{2/2}$ spots, etc.

A Before installing, check whether the fuel injector nozzle gasket has been replaced and installed on the STATE STATE STATE STATE STATE STATE STATE STATE fuel injector.

When installing the fuel injector, apply lubricant between the fuel injector, fuel nozzle sealing gasket and O-ring, The second a and the

Without replacing new gasket can lead to: deformation of the tight cap of nozzle, deformation of nozzle, deformation of nozzle orifice, oil leakage and air leakage, which will cause serious damage to the fuel injector and nozzle to break and cause damage to the engine.

A When installing the injector on the engine, please carefully check the components related to the installation of the injector, such as the injector pressure plate, screw, injector rod and other accessories are not deformed, and install it in strict accordance with the operation steps of the engine maintenance manual. It is forbidden to operate the bare injector for a long time in an environment with serious dust pollution and corrosion to iron products. -SAUDA $\mathcal{D}^{\mathbb{N}_{+}}$

It is forbidden to operate the bare injector for a long time in a strong magnetic field environment.

2.4. 0445110107 **Injector 's Reasons for Not Working Normally** (1) There is air in the cill circuit.

(1) There is air in the oil circuit of the engine fuel system.

(2) Vehicle oil pump oil supply system is not normal.

ahi^{ngh} (3) Engine common rail system oil leakage or pressure limiting valve damage.

(4) There is a short circuit, cutting out and poor contact in the wiring harness connected to the fuel injector - sthat 57^{8,300} Star . of the vehicle.

(5) The long-term placement of the injector causes the anti-rust oil to solidify, and the internal components SANDAR C SPARTER T are stuck or the oil holes are blocked.

Before installing, carefully check whether other components in the common rail system except the fuel injector are damaged so as to prevent the fuel injector from not working properly after being replaced. Stream Stream Stream

2.5. 0445110107 Injector 's Causes of Damage

(1) Didn't operate properly according to engine maintenance manual during disassembly or installation, resulting in damage to the injector .

(2) The fuel oil used for the vehicle does not meet the standard cause damage to the injector, such as the water content in the fuel oil exceeds the standard, iron powder, aluminum powder, sulfide impurities exceed the standard, etc.

(3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating oil of the engine system for a long time will cause abnormal wear of the engine, excessive exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced during maintenance or the replaced filter cannot reach the original filter standard. all above reasons can cause damage to the injector.

(4) The abrasion of the oil pump produces iron powder and aluminum powder enter the fuel injector and cause damage to the fuel injector.

(5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the fuel

injector and causing damage to the fuel injector.

(6) The fuel injector is damaged due to replacement or adjustment of the relevant parts of the fuel injector. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the injector fails to meet the original standard.

- (7) The engine is overheated and overloaded for a long time working results in damage to the fuel injector.
- (8) The injector will be damaged naturally at the end of its working life.

(9) The injector is magnetized (injector parts' magnetic exceeded) causing the injector to not work properly. A Before replacing the fuel injector, please check the engine parts carefully according to the engine maintenance manual to avoid the fuel injector being damaged again after replacement.

2.6.0445110107 Injector's Technical Support Obtaining Methods

- (1) Injector Technical File, visit http://shumatt.com to get the technical file.
- (2) Injector Technical Videos

25⁵ 100 and. Facebook: Visit https://www.facebook.com/hison.li to get the technical videos, constantly follow can get more information.

YouTube: https://www.youtube.com/channel/UCByvYBx7VjV_mAfxh_Hu-aw to get the technical videos, constantly follow can get more information.

Shumatt: Visit <u>http://shumatt.com</u> to get the technical videos.

(3) Injector Information Query Software

TruckBook Parts EPC APP, Android/Apple App Store download and install, visit http://shumatt.com to get the download and installation tutorial

(4) Search The fuel injector test data through TruckBook Parts EPC APP.

100

3.0445110107 Injector's Purchase and Delivery 17 Star $\mathcal{P}_{\mathcal{P}_{\mathrm{S}}}$

11 Car and the second 3.1.0445110107 Injector's Purchase Payment Term

Payment Terms: T/T, PayPal, Alipay, WeChat

Please contact our salesmen for specific payment information.

3.2.0445110107 Injector's Main Sales Markets

120 d de Injector main sales markets: Asia, Europe, North America, South America, Africa etc.

3.3.0445110107 Injector's Declaration Requirements

anti la Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc. a soft 2.5055 ast in the

3.4.0445110107 Injector's Shipping Ways

Destination in China areas: SF Express, Debon Express, the corresponding logistics company can be provided Sh Sor $S^{h^{S^{O}}}$ according to customer requirements in special cases. Destinations out of China's areas: DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

3.5.0445110107 Injector's Lead time

Mob/WhatsApp: +86 13410541523 Email:ruby@shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd

Lead time: Send out within 3 – 7 working days after receiving payment (Except for special products and SHAMPY S. A. DER STREEP SPR. FRE -1000 SHUDDES special cases).

Country or Region of Departure Hong Ko China China's Mainland 7 Day		ng, Other Countries or Regions of Asia	Australia and New Zealand		Europe	America	Other Countries	
		7 Days	7 Days	8 Days		8 Days	8-12 Days	7-10 Days
IPS Logistics Ti	me:	Country	or Region of Departure	e: China's Ma	inlanc	de la	din da	Sterne B
Country of Destination		mated al Time	Country of Destination	Estimated Arrival Time	Соц	untry of Desti	nation	Estimated Arrival Time
Japan	3 [Days	UK UK	5-7Days	el.	Egypt	di .	5-7 Days
Turkey	5-7	Days	Singapore	3 Days	5113	Switzerland	i st ^{ar}	5-7 Days
Bahrain	5-7	Days	Latvia	7-10 Days	T	New Zealan	d	7-10 Days
Sri Lanka	5-7	Days	Thailand	3 Days	100	Austria	الكري المح	5-7 Days
Romania	5-7	Days	Vietnam	3-5 Days		Estonia		5-7 Days
Malaysia	3-5	Days	st srael	5-7 Days	ri. . n ⁴⁶	Mexico	6 ¹⁴	7-10 Days
France	5-7	Days	America	5-7 Days	Ur	nited Arab Em	irates	5-7 Days
Italy	5-7	Days	Netherlands	5-7 Days	÷.,	Bengal	de de	7-10 Days
Lebanon	5-7	Days	Philippine	3-5 Days	$S_{P_{2}}$	Greece	Store and	7-10 Days
South Korea	3 [Days	Spain	5-7 Days	Ŷ	Myanmar		5-7 Days
Canada	5-7	Days	Germany	5-7 Days	Ships	Saudi Arabi	a _{Sh} sh	7-10 Days
Portugal 5-7 Days		Days	Australia 5-7 Days		South Africa		7-10 Days	
Denmark	5-7	Days	Belgium	5-7 Days	all.	Ukraine	8°	7-10 Days
India	7-10) Days	Qatar	7-10 Days	50	Poland	80.	5-7 Days
Indonesia	3-5	Days	Morocco	7-10 Days	1. 	Pakistan	1	7-10 Days
Kuwait	7-10) Days	1987 - 1987 - 19	Store Star	- Store	51	2000	S. Carlor

3.6.0445110107 Injector's Logistics Time for Destination Out of China's Areas

The logistics time is for reference only, subjects are according to the actual arrival. All All C

3.7.0445110107 Injector's Packing

Domestic express packaging: Usually wrapped in waterproof scotch tape, such as picture No.2. International express packaging: Wrapped with waterproof yellow tape After wrapping the black protective film, such as picture No. 3.

Pallet Shipping: Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 4, SPACENT

also, the products can be packaged according to customers' requirements.

The packing tray is made of plastic and can be recycled.


Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are non-degradable materials, please dispose of them properly. SALEST

Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury.

SPASSAR

THE THE STREET STREET STREET STREET STREET

Mob/WhatsApp: +86 13410541523 Email : ruby@shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd



Pallet Shipping: Use pallet that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties and and a start and the

4.0445110107 Injector's Storage Standard

(1) Choose a suitable storage place

1795 The warehouse and cargo yard where the fuel injector is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acid, alkali, salt and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir area dry. $\otimes^{\mathbb{N}^{|\mathcal{G}|}}$ States

(2) Strict requirements of warehousing

Strict inspections should be carried out when the fuel injectors are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ash and other dirt, remove the rust and do antirust treatment in time. Packaged injectors must be protected from damage.

(3) Keep the warehouse dry and preventing moisture

Mob/WhatsApp: +86 13410541523 Email:ruby@shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd 1.000 C

The relative humidity is usually below 70% for the fuel injectors placed in the room, and the corrosion of the fuel injectors is significantly reduced.

Injectors must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

(4) Stack Properly

After the injector is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse

If the fuel injector package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.

- **A** It is forbidden to leave the injector exposed in the air for a long time.
 - It is forbidden to store acid, alkali, salt and other substances together with the injector.
 - A The unpacked fuel injector must be rust-proof during secondary storage.

5. Company Information



Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

Email: ruby@shumatt.com

Website: www.shumatt.net

Shenzhen Office: 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

Shenzhen Office: Room 428-430, Building B, Huafeng Zhigu Technology Industrial Park, Exit B, Fuyong Metro Station, Bao'an District, Shenzhen, China's Mainland

♥ Hong Kong Office: Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

• After-sales Service Address: Please contact our salesmen to obtain and provide the corresponding product maintenance reasons (Reference: <u>1.10.0445110107 Injector Warranty Instructions</u>)

No.	Name WeChat/WhatsA		Email	Facebook	YouTube	
1	Ruby	+86-13410541523	ruby@shumatt.com	Hison Li	Hison Li	
2	lvy	+86-18025299821 sales@shumatt.com		Ivy Shumatt	Shumatt IVY	
3	Rebecca	+86-18025349821	sales01@shumatt.com	Rebecca SHUMATT	SHUMATT Rebecca	
4	Janny	+86-18028749821	sales02@shumatt.com	Janny shumatt	Janny Shumatt	
5	Sam	+86-13316859821	Sales8@shumatt.com	Shumatt Sam	Sam Shumatt	
6	Natalie	+86- 18938945856	sales15@shumatt.com	Shumatt Natalie	Lin Natalie	
7	Ada	+86-1342286353	sales5@shumatt.com	Shumatt Ada	Ada Shumatt	
8	Hison Li	+86-18318811871	web@shumatt.com	Hison Li	Hison Li	
9.00	Mecca	+86-18938948618	sales11@shumatt.com	Shumatt Mecca	Shumatt Mecca	
10	ST Eric S	+86 18319033618	sales3@shumatt.com	Str. Str.	1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 -	
11	Wayne (Joaquín en español)	+86-13316959821	wayne@shumatt.com	shumattwayne	Wayne Shumatt	
12	Sylvia	+86 18312499884	sales6@shumatt.com	all all	and the second	
31	- STA - STA - ST	Call have flat was a set	tain the latest information of sales-m	2000 - 0000	500° - 50°	

5.2. Sales-men's Contact Information

6. Copyright Statement

The copyright of any contents (including but not limited to parameters, data, text, charts, images, sounds or videos, etc.) provided in "0445110107 *Injector* CRI1-13 *Technical File*" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "0445110107 *Injector* CRI1-13 *Technical File*" in any way. At the same time, any conditions to spread, re-post, display the contents of "0445110107 *InjectorCRI1-13Technical File*" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "0445110107 *Injector* CRI1-13 *Technical File*" will violate the "*Copyright Law of the People's Republic of China*" and other laws and regulations and the provisions of relevant international parametians.

States.

SPATTER

519320

SPREEDENT

519.39505

conventions. $a^{\mu \prime}$

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd