

SHUMBITT

0445110170 Injector CRI1-13 Technical File

SKU1: G1W20445110170











0445110170 Injector CRI1-13 Technical File

Content

1.0445110170 Injector's Introduction			2
1.1. 0445110170 Injector's Basic Information			2
1.2. 0445110170 Injector's Common Part Number	30	34 34	2
1.3.0445110170 Injector's Matching Information			3
1.4.0445110170 Injector's Parameter	91,550	41. S	4
1.5.0445110170 Injector's Specifications and Dimensions			4
1.6. 0445110170 Injector's Quality Control			
1.6. 0445110170 Injector's Quality Control	587	\$57°° \$5	2
1.8.0445110170 Injector's Packing List and Package Size			
1.9.0445110170 Injector's Testing Standard and Certificate	- 13 July 1		6
1.10.0445110170 Injector's Warranty Instructions			7
1.11.0445110170 Injector's Manufacturer			8
2.0445110170 Injector Technical Support	37	37° 3	8
2.1.0445110170 Injector's Part Number Location			
2.2.0445110170 Injector's Application Scenarios			8
2.3.0445110170 Injector's Installation			
2.4. 0445110170 Injector 's Reasons for Not Working Normally			
2.5. 0445110170 Injector 's Causes of Damage	82,	811 81	10
2.6.0445110170 Injector's Technical Support Obtaining Methods			
3.0445110170 Injector's Purchase and Delivery	200,200	gilli ^{gar} i g	11
3.1.0445110170 Injector's Purchase Payment Term			11
3.2.0445110170 Injector's Main Sales Markets			11
3.1.0445110170 Injector's Purchase Payment Term	\$57°	200. 20	11
3.4.0445110170 Injector's Shipping Ways			
3.5.0445110170 Injector's Lead time		gilirg	11
3.6.0445110170 Injector's Logistics Time for Destination Out of China's			
3.7.0445110170 Injector's Packing			12
4.0445110170 Injector's Storage Standard	394.	94. 9	13
5. Company Information	S		14
5.1. Company Introduction	200 m	A Section	14
5.2. Sales-men's Contact Information			15
6. Copyright Statement			15
20. 20. 20. 20. 20. 20. 20. 20.	(90)	Jan. Jan.	V. 1984.
THE PERSON NAMED IN COLUMN TO STREET THE PERSON NAMED IN COLUMN TO STREET THE PERSON NAMED IN COLUMN TO STREET	s. Landingstra	and the second	
Dit Dit Dit Dit Die Die Jay, Jay, Jay, Jay,	511	Dr.1 (24)	34.
Margaria Margaria Margaria Margaria Margaria Margaria Margaria Margaria	alphanic.	Shyanger S	Harris Ali
THE THE THE THE THE THE THE THE THE	·	1774cm.	· Philips.

Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com

© 2022 Shenzhen Shumatt Technology Co., Ltd

Website: www.shumatt.com

Tel: +8675523215133



0445110170 Injector CRI1-13 Technical File

1.0445110170 Injector's Introduction

1.1. 0445110170 Injector's Basic Information

Title Title	China made new high quality diesel injector 0445110170 fuel injector CRI1-13
SKU 1	G1W20445110170
SKU 2	

1.2. 0445110170 Injector's Common Part Number

(1) Injector's Exchange Information

Injector Part Number	Re-manufactured Part Number				
0445110170	0 986 435 053				
0 445 110 171	0 986 435 164				
0 445 110 181					
0 445 110 182	CONTROL OF THE PARTY OF THE PAR				

(2) Injector's Application Information

Injector Part Number	MERCEDES-BENZ Car Model	DODGE	FREIGHTLINER	MERCEDES- BENZ
- Mar 1	612 070 03 87		- 100	
0 445 110 171	A 612 070 03 87		Company of the same of the sam	AND STATE OF THE STATE OF
50.0 443 £40 171 50.	611 070 12 87	29.6. 29.6.	.pupupu.	34. 34.
	A 611 070 12 87	See The The	The Think	att of the same
all all all	612 070 03 87	40000	31, 31, 31,	979
0 445 110 170	A 612 070 03 87	- 120 - 120 - 120 -	a sate sate	72m 22m
St. 311011.0	611 070 12 87	m, athur, athur,	Supplies Supplies Sup	100 April 100
	A 611 070 12 87	- T	4 .4 .4	
Christian Christian Ch	612 070 04 87	05135 154AA	R5135154AB	
	R5135154AB	R5135154AB		
AND THE PARTY AND THE PARTY.	612 070 04 87 0080	5135 154AA	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	OFF WHAT IS
20, 20, 30	A 612 070 04 87 80	201. 201.	301. 301. 301.	397, 397,
CONTY CONTY	612 070 04 87 80	1775 milit	The Theory	The The
0 986 435 053	A 612 070 03 87	310. 310.	24. 24. 24.	31000 310
770 m	A 612 070 04 87 0080			
strange, strange, st	A 612 070 03 87 80	alpha, alpha,	Styles Styles Sty	31g 31g
3 3	A 612 070 04 87			
	612 070 03 87		APP APP A	Mr. all Mr. all
	612 070 03 87 80			
THE THE PARTY AND THE PARTY AN	612 070 03 87		Carried Control of Con	STATE WASHINGTON
0 986 435 164	A 612 070 03 87	Att. Att.	20. 20. 20.	39. 38.
Marin Marin	611 070 12 87 80	Time Time Time	Mary Mary M	Mary Mary

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com Website: www.shumatt.com

			,,	
31 31	612 070 03 87 80	~ ~ ~	× × ×	-S -S
aligner, algebra al	A 611 070 12 87	an alpan, alpan	at the state of	an, Shape, Sh
	A 611 070 12 87 80			
STATES STATES	A 612 070 03 87 80		and the contract of	
	611 070 12 87		D- D- D-	
THE PERSON OF THE PERSON OF	612 070 04 87	R5135154AB	R5135154AB	and a series
811 S11 911	A 612 070 04 87	50° 50°	31. 31. 31.	300- 300-
0 445 110 181	R5135154AB	See The The	1 Jac. 1966. 1	Mary Mary
stran stran st	612 070 03 87	. sh. sh.	style style sty	30° 31° 31° 31°
25 25	A 612 070 03 87	ar ar a	a at at	25. 25.
Stranger, Stranger, St.	612 070 04 87	athan athan.	Stranger, Stranger, St.	
0.445 110 103	A 612 070 04 87			
0 445 110 182	612 070 03 87	SELLE THE PERSON OF THE PERSON		
N1 N1 N1	A 612 070 03 87	200 300	31 31 31	201 201

(3) Injector's Part Number Common Writing

0445110171, 0445110170, 0445110181, 0445110182, 0986435053, 0986435164, $0.445\ 110\ 171$, $0.445\ 110\ 170$, $0.445\ 110\ 181$, $0.445\ 110\ 182$, $0.986\ 435\ 053$, $0.986\ 435\ 164$, 0 445 110171,0 445 110170,0 445 110181,0 445 110182,0 986 435053,0 986 435164, 0 445110171, 0 445110170, 0 445110181, 0 445110182, 0 986435053, 0 986435164, 0445 110 171, 0445 110 170, 0445 110 181, 0445 110 182, 0986 435 053, 0986 435 164, 0445110 171, 0445110 170, 0445110 181, 0445110 182, 0986435 053, 0986435 164, 0445 110171, 0445 110170, 0445 110181, 0445 110182, 0986 435053, 0986 435164, A 612 070 03 87 80, A612070038780, 612 070 03 87 80, 612070038780, A 612 070 03 87, A6120700387, 612 070 04 87 0080, 61207004870080, 612 070 04 87 80, 612070048780, A 612 070 04 87, A6120700487, A 611 070 12 87 80, A611070128780, 611 070 12 87, 6110701287, A 611 070 12 87, A6110701287, 612 070 04 87, 6120700487, A 612 070 04 87 80, A612070048780, A 612 070 04 87 0080, A61207004870080, 611.070 12 87 80, 611070128780, 612 070 03 87, 6120700387, 05135 154AA, 05135154AA, 5135 154AA, 5135154AA, R5135154AB

1.3.0445110170 Injector's Matching Information

vehicle brand	Series	Car Model	Engine Model	Production date	Power (KW)	emission standard	Horse power	Manufacturer	Emission	Cylinder	Power Source (V)
MERCEDES -BENZ	Sprinte r [T1N	216 CDI Sprinte r	OM 612.981 D LA	04/2000 - 05/2006	115 kW	156 PS	/	/	/	5	12
MERCEDES -BENZ	Sprinte r [T1N]	316 CDI Sprinte r	OM 612.981 D LA	04/2000 - 05/2006	115 kW	156 PS	/	/	/	5	12
MERCEDES -BENZ	Sprinte r [T1N]	316 CDI Sprinte r James	OM 612.981 D LA	04/2001 - 05/2006	115 kW	156 PS	/	/	/	5	12

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133

Website: www.shumatt.com Email: ruby@shumatt.com

SHUMATT

Shenzhen Shumatt Technology Co., Ltd

		Cook									
MERCEDES -BENZ	Sprinte r [T1N]	416 CDI Sprinte r	OM 612.981 D LA	04/2000 - 05/2006	115 kW	156 PS	/	/	/	5	12
MERCEDES -BENZ	Sprinte r [T1N]	616 CDI Sprinte r	OM 612.981 D LA	02/2001 - 05/2006	115 kW	156 PS	/	/	/	5	12

1.4.0445110170 Injector's Parameter

Adaptation System: Common Rail System

Injector Series: 110 Series

Parameter Performance: CRI1-13

Matching Accessories:

Injector Type: Electromagnetic Injector
Support System Maximum Pressure: 1350

Vehicle Configuration Information: MERCEDES-BENZ/DODGE/FREIGHTLINER/MERCEDES-BENZ

1.5.0445110170 Injector's Specifications and Dimensions

Injector Size: 21.5cm*4 cm *4 cm = 344cm3 (L*W*H=V)

Injector Net Weight: 0.55kg

Gross Weight: 0.6kg

Injector Quality: China Made Brand New
Package Size: 28cm*7 cm *7 cm = 1372 cm³
Injector Type: Diesel Common Rail Injector

MOQ: 4 Pieces

1.6. 0445110170 Injector's Quality Control

(1) Injector Testing

All injector spare parts are tested for electrical characteristics, accuracy, high temperature, low temperature, withstand voltage, leakage, durability, and various working conditions.

(2) Injector Assembling

And the quality control of the injector production and installation process, our company strictly follows the standard product installation data and product installation steps to install, such as injector stroke test, injector solenoid valve tightening torque, injector nozzle tightening torque,

(3) Injector Inspection

The factory inspection of the injector is undergone full inspection, random inspection, and batch inspection three inspections. Different brands of test benches are used to test the same fuel injector for a total of no less than three times for factory inspection, and the fuel injector installation testing environment are progressed in dust-free workshop.

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com Website: www.shumatt.com



1.7. 0445110170 Injector's Customized Service

(1) Injector's Customized Service: Meet the customized needs of OEM manufacturers for shell lettering, logo engraving, injector internal packaging, injector external packaging and labels customized, etc.



(2) Injector's Customized Service Requirements:

The purchased of customized injector are not less than 10 pieces.

Customized injector packages no less than 1000 pieces.

Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file.

▲ Once the customized fuel injector is sold, it cannot be returned or exchanged if there is no quality problems.

53^{0,377} 1.8.0445110170 Injector's Packing List and Package Size

(1) Injector Spare Parts List

No.	25 25 1 25 25 25 25 E	2	2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Image	Shoma	KEL SHIRE OF SHIRESE	ant O ant
Name	Fuel Injector	O-Ring	Gasket F 00V C17 503
Description No.	Fuel injector part number: 0445110170	Ensure to meet the standard of the sealing performance between the injector and the engine	Made of brass, used to ensure the tight fit between the injector cap end and the engine
Image	TI SHOW SHOW	SETT SETT	SHEET SHE
200 Til	o L	177	17
Name	Nozzle Protective Cover Cap	Injector House Protective Cover Cap	Solenoid Valve Protective Cap
Description	Protect nozzle holes from being polluted and blocked	Protect oil inlet from being polluted and blocked	Protect the solenoid valve body and terminals from being damaged by external forces
No.	3 T 3 T 3 T 3 T 3 T 3 T 3 T 3 T 3 T 3 T	3400 3800 34000	
Image No.	2	et.	51 ⁰
Name	VCI Anti-rust Bag	Bubble Bag	Injector Packing Box
Description	Prevent fuel injector from rusting	Prevent the injector from being damaged by external forces	Place injector and injector accessories

▲ Minors are forbidden to use the fuel injector assembly, O-ring, gasket, nozzle protective cover, fuel injector house protective cover, solenoid valve protective cover, VCI anti-rust bag, and air bubble bag to avoid personal injury.

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com Website: www.shumatt.com



- ▲ O-ring and gasket are disposable installation accessories, and need to be replaced for re-installation.
 - ▲ The nozzle protective cover, the injector house protective cover, and the solenoid valve protective cover are recyclable accessories that can be reused.
 - ▲ VCI anti-rust bags and bubble bags are non-degradable materials, please dispose of them properly after using.
- ▲ The injector and the installation parts should be coated with appropriate sealing oil during installation.

(2) Injector Box Size



gi	No.	Name	2.00	Injector Package	Size (cm)	L. 2111	0.1117
	1	Injector Box	A A	28*7*:	7		4 24

1.9.0445110170 Injector's Testing Standard and Certificate

We can provide the factory quality inspection test report of each injector to ensure that each injector delivered meets the engine performance indicators.



Mob/WhatsApp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com

© 2022 Shenzhen Shumatt Technology Co., Ltd

Website: www.shumatt.com



1.10.0445110170 Injector's Warranty Instructions

(1) . Product Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the injector inspection equipment when the injector is abnormal during use as evidence to feed back to the salesman.

Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting the engine, 4. Engine noise, 5. oil leakage etc.

(2) . Injector Warranty Coverage

Within 15 days after customer receives the 0445110170 injector, if there is a performance failure and the product has no appearance damage, customer can choose to replace it or repair it;

If the 0445110170 injector has performance problems during the warranty period (3 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

If the injector house has obvious scratches, it can only be repaired and it will be returned as it is if the product is confirmed to be fault-free.

▲ Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 months from the date of repairing.

(3) Injector Out of Warranty Coverage

The warranty period has expired.

Injector failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, earthquake, and used in abnormal environment.

Customer disassembles or repairs the injector personally resulting in damage to the injector.

Injector damage caused by man-made reasons (throwing, strong magnetic field magnetization, set fire).

Injector failure or injector damage caused by non-injector design, technology, manufacturing, quality and other issues.

Injector failure due to system pressure exceeding system approved pressure.

Injector failure caused by system voltage exceeding approved voltage.

Injector failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in the system

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com Website: www.shumatt.com

fuel exceeding the standard requirements.

Injector failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).

Injector failure caused by not following the installation angle specified in the vehicle engine maintenance manual.

Injector failure caused by not following the cleaning requirements specified in the vehicle engine maintenance manual.

Injector failure caused by failure to replace consumable parts as specified in the vehicle engine maintenance manual.

Injector failure caused by not complying with the intake system fit clearance and exhaust system fit clearance requirements specified in the vehicle engine maintenance manual.

Failure to replace the consumable parts and the fitting clearance of the oil inlet system pipeline and the fuel injector connection in accordance with the fuel intake system specified in the vehicle engine maintenance manual.

1.11.0445110170 Injector's Manufacturer

Injector's manufacturer: Shenzhen Shumatt Technology Co., Ltd

2.0445110170 Injector Technical Support

2.1.0445110170 Injector's Part Number Location

1) E.g.: The injector part number see as follows



No.	Name						
A A	brand, logo, part number, series number						
В	nozzle part number						


2.2.0445110170 Injector's Application Scenarios

Common rail system is an oil supply method refers to the diesel oil from the fuel tank sucked out by the gear pump through the oil-water separator and the gear pump to diesel fine filter, high-pressure pump, common rail pipe, and fuel injector, all together with the closed-loop fuel supply system composed of sensors and ECU that completely separates the generation of injection pressure and the injection process from each other.

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com Website: www.shumatt.com





Pic No. 1

No.	Name	No.	Name	No.	Name	No.	Name
1	Tank	5	Common Rail Pressure Sensor	9	Engine Crankshaft Sensor	A.	High Pressure Oil Circuit
2	Diesel Filter	6	Common Rail Pipe	10	Camshaft Sensor	В	Low Pressure Oil Circuit
3	High-Pressure Pump	رة 7	Injector	11	ECU Electronic Control Unit	-offi	-10TE -10TE
-4	Fuel Gear Pump	8	Accelerator Pedal	California .	AND THE STATE OF		

2.3.0445110170 Injector's Installation

(1) .0445110170 Injector's Installation Precautions:

A The replacement of the fuel injector must strictly follow the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter and the high-pressure fuel circuit) specified in the vehicle engine maintenance manual,

A Replacement of wearing parts of the fuel system, cleaning requirements for the connection between the fuel system and the injector, the fitting clearance of the fuel injector connection, the installation angle and tightening torque of the injector, the fitting clearance of the intake system, and the fitting clearance of the exhaust system to ensure the service life of the engine and the normal operation of the injector.

A When installing the fuel injector on the engine, it is necessary to clean the engine block, cylinder head and other parts connected to the fuel injector, and ensure that there is no dust, carbon deposits, water, rust spots, etc.

▲ Before installing, check whether the fuel injector nozzle gasket has been replaced and installed on the fuel injector.

▲ When installing the fuel injector, apply lubricant between the fuel injector, fuel nozzle sealing gasket and O-ring.

▲ Without replacing new gasket can lead to: deformation of the tight cap of nozzle, deformation of nozzle, deformation of nozzle orifice, oil leakage and air leakage, which will cause serious damage to the fuel injector and nozzle to break and cause damage to the engine.

▲ When installing the injector on the engine, please carefully check the components related to the installation of the injector, such as the injector pressure plate, screw, injector rod and other accessories are not deformed, and install it in strict accordance with the operation steps of the engine maintenance manual.

▲ It is forbidden to operate the bare injector for a long time in an environment with serious dust pollution and corrosion to iron products.

▲ It is forbidden to operate the bare injector for a long time in a strong magnetic field environment.

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com Website: www.shumatt.com



2.4. 0445110170 Injector 's Reasons for Not Working Normally

- (1) There is air in the oil circuit of the engine fuel system.
- (2) Vehicle oil pump oil supply system is not normal.
- (3) Engine common rail system oil leakage or pressure limiting valve damage.
- (4) There is a short circuit, cutting out and poor contact in the wiring harness connected to the fuel injector of the vehicle.
- (5) The long-term placement of the injector causes the anti-rust oil to solidify, and the internal components are stuck or the oil holes are blocked.
- ▲ Before installing, carefully check whether other components in the common rail system except the fuel injector are damaged so as to prevent the fuel injector from not working properly after being replaced.

2.5. 0445110170 Injector 's Causes of Damage

- (1) Didn't operate properly according to engine maintenance manual during disassembly or installation, resulting in damage to the injector .
- (2) The fuel oil used for the vehicle does not meet the standard cause damage to the injector, such as: the water content in the fuel oil exceeds the standard, iron powder, aluminum powder, sulfide impurities exceed the standard, etc.
- (3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating oil of the engine system for a long time will cause abnormal wear of the engine, excessive exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced during maintenance or the replaced filter cannot reach the original filter standard. all above reasons can cause damage to the injector.
- (4) The abrasion of the oil pump produces iron powder and aluminum powder enter the fuel injector and cause damage to the fuel injector.
- (5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the fuel injector and causing damage to the fuel injector.
- (6) The fuel injector is damaged due to replacement or adjustment of the relevant parts of the fuel injector. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the injector fails to meet the original standard.
- (7) The engine is overheated and overloaded for a long time working results in damage to the fuel injector.
- (8) The injector will be damaged naturally at the end of its working life.
- (9) The injector is magnetized (injector parts' magnetic exceeded) causing the injector to not work properly.
- A Before replacing the fuel injector, please check the engine parts carefully according to the engine maintenance manual to avoid the fuel injector being damaged again after replacement.

2.6.0445110170 Injector's Technical Support Obtaining Methods

- (1) Injector Technical File, visit http://shumatt.com to get the technical file.
- (2) Injector Technical Videos

Facebook: Visit https://www.facebook.com/hison.li to get the technical videos, constantly follow can get more information.

YouTube: https://www.youtube.com/channel/UCByvYBx7VjV mAfxh Hu-aw to get the technical videos, constantly follow can get more information.

Shumatt: Visit http://shumatt.com to get the technical videos.

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com Website: www.shumatt.com



. Tro. Tro.

Shenzhen Shumatt Technology Co., Ltd

(3) Injector Information Query Software

TruckBook Parts EPC APP, Android/Apple App Store download and install, visit http://shumatt.com to get the download and installation tutorial

(4) Search The fuel injector test data through TruckBook Parts EPC APP.

3.0445110170 Injector's Purchase and Delivery

3.1.0445110170 Injector's Purchase Payment Term

Payment Terms: T/T, PayPal, Alipay, WeChat

Please contact our salesmen for specific payment information.

3.2.0445110170 Injector's Main Sales Markets

Injector main sales markets: Asia, Europe, North America, South America, Africa etc.

3.3.0445110170 Injector's Declaration Requirements

Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

3.4.0445110170 Injector's Shipping Ways

Destination in China areas: SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

Destinations out of China's areas: DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

3.5.0445110170 **Injector's Lead time**

Lead time: Send out within 3 – 7 working days after receiving payment (Except for special products and

3.6.0445110170 Injector's Logistics Time for Destination Out of China's Areas

DHL Logistics Time:

Country or Region of Departure	Hong Kong, China	Other Countries or Regions of Asia			America	Other Countries
China's Mainland	7 Days	7 Days	8 Days	8 Days	8-12 Days	7-10 Days

UPS Logistics Time: Country or Region of Departure: China's Mainland

Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time
Japan	3 Days	UK	5-7Days	Egypt	5-7 Days
Turkey	5-7 Days	Singapore	3 Days	Switzerland	5-7 Days
Bahrain	5-7 Days	Latvia	7-10 Days	New Zealand	7-10 Days
Sri Lanka	5-7 Days	Thailand	3 Days	Austria	5-7 Days
Romania	5-7 Days	Vietnam	3-5 Days	Estonia	5-7 Days
Malaysia	3-5 Days	Israel	5-7 Days	Mexico	7-10 Days
France	5-7 Days	America	5-7 Days	United Arab Emirates	5-7 Days
Italy	5-7 Days	Netherlands	5-7 Days	Bengal	7-10 Days

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com Website: www.shumatt.com

Lebanon	5-7 Days	Philippine	3-5 Days	Greece	7-10 Days
South Korea	3 Days	Spain	5-7 Days	Myanmar	5-7 Days
Canada	5-7 Days	Germany	5-7 Days	Saudi Arabia	7-10 Days
Portugal	5-7 Days	Australia	5-7 Days	South Africa	7-10 Days
Denmark	5-7 Days	Belgium	5-7 Days	Ukraine	7-10 Days
India	7-10 Days	Qatar	7-10 Days	Poland	5-7 Days
Indonesia	3-5 Days	Morocco	7-10 Days	Pakistan	7-10 Days
Kuwait	7-10 Days	720 The 1720	Sec. Page	1 200	27s. 27s

The logistics time is for reference only, subjects are according to the actual arrival.

3.7.0445110170 Injector's Packing

Domestic express packaging: Usually wrapped in waterproof scotch tape, such as picture No.2.

International express packaging: Wrapped with waterproof yellow tape After wrapping the black protective film, such as picture No. 3.

Pallet Shipping: Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 4, also, the products can be packaged according to customers' requirements.

▲ The packing tray is made of plastic and can be recycled.

▲ Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are non-degradable materials, please dispose of them properly.

Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury.



Domestic express packaging:

Wrapped with Transparent tape



Pic No. 3

International express packaging:

Wrapped with yellow tape after wrapping black protective film

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com Website: www.shumatt.com © 2022 Shenzhen Shumatt Technology Co., Ltd





Pic No. 4

Pallet Shipping: Use pallet that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties

4.0445110170 Injector's Storage Standard

(1) Choose a suitable storage place

The warehouse and cargo yard where the fuel injector is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acid, alkali, salt and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir area

(2) Strict requirements of warehousing

Strict inspections should be carried out when the fuel injectors are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ash and other dirt, remove the rust and do antirust treatment in time. Packaged injectors must be protected from damage.

(3) Keep the warehouse dry and preventing moisture

The relative humidity is usually below 70% for the fuel injectors placed in the room, and the corrosion of the fuel injectors is significantly reduced.

Injectors must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

(4) Stack Properly

After the injector is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse Black.

If the fuel injector package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.

▲ It is forbidden to leave the injector exposed in the air for a long time.

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com Website: www.shumatt.com

- It is forbidden to store acid, alkali, salt and other substances together with the injector.
- The unpacked fuel injector must be rust-proof during secondary storage.

5. Company Information



5.1. Company Introduction

Chinese Name: 深圳市舒马特科技有限公司

English Name: Shenzhen Shumatt Technology Co., Ltd

Mob Phone/WeChat: +86-13410541523

☐ **HK Telephone**: +852-67653519

Telephone: +86-755-23215133

Email: ruby@shumatt.com

Website: www.shumatt.net

Shenzhen Office: 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

Shenzhen Office: Room 428-430, Building B, Huafeng Zhigu Technology Industrial Park, Exit B, Fuyong Metro Station, Bao'an District, Shenzhen, China's Mainland . Mar Mar Mar Mar

AND THE PARTY OF T

Hong Kong Office: Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133

Email: ruby@shumatt.com

© 2022 Shenzhen Shumatt Technology Co., Ltd

14 / 15

Website: www.shumatt.com

After-sales Service Address: Please contact our salesmen to obtain and provide the corresponding product maintenance reasons (Reference: 1.10.0445110170 Injector Warranty Instructions)

5.2. Sales-men's Contact Information

No.	Name	WeChat/WhatsApp	Email	Facebook	YouTube		
11	Ruby	+86-13410541523	ruby@shumatt.com	Hison Li	Hison Li		
2, 1000	lvy 3000	+86-18025299821	sales@shumatt.com	Ivy Shumatt	Shumatt IVY		
3	Rebecca	+86-18025349821	sales01@shumatt.com	Rebecca SHUMATT	SHUMATT Rebecca		
4	Janny	+86-18028749821	sales02@shumatt.com	Janny shumatt	Janny Shumatt		
5	Sam	+86-13316859821	Sales8@shumatt.com	Shumatt Sam	Sam Shumatt		
6	Natalie	+86- 18938945856	sales15@shumatt.com	Shumatt Natalie	Lin Natalie		
7	Ada	+86-1342286353	sales5@shumatt.com	Shumatt Ada	Ada Shumatt		
8	Hison Li	+86-18318811871	web@shumatt.com	Hison Li	Hison Li		
9	Mecca	+86-18938948618	sales11@shumatt.com	Shumatt Mecca	Shumatt Mecca		
10	Eric	+86 18319033618	sales3@shumatt.com	3			
11	Wayne (Joaquín en español)	+86-13316959821	wayne@shumatt.com	shumattwayne	Wayne Shumatt		
12	Sylvia	+86 18312499884	sales6@shumatt.com	Character Character	St. St.		
Visit http://shumatt.com to obtain the latest information of sales-men							
PS: Shumatt's sales-men's emails are all end with @shumatt.com							

6. Copyright Statement

The copyright of any contents (including but not limited to parameters, data, text, charts, images, sounds or videos, etc.) provided in "0445110170 *Injector CRI1-13 Technical File*" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "0445110170 *Injector CRI1-13 Technical File*" in any way. At the same time, any conditions to spread, re-post, display the contents of "0445110170 *InjectorCRI1-13Technical File*" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "0445110170 *Injector CRI1-13 Technical File*" will violate the "Copyright Law of the People's Republic of China" and other laws and regulations and the provisions of relevant international conventions.



Mob/WhatsApp: +86 13410541523 Tel: +8675523215133

© 2022 Shenzhen Shumatt Technology Co., Ltd

Email: ruby@shumatt.com

15 / 15

Website: www.shumatt.com