

0445110457 Injector CRI2-16 Technical File

SKU1:









0445110457 Injector CRI2-16 Technical File

Content

1.0445110457 Injector's Introduction	2
1.1. 0445110457 Injector's Basic Information	2
1.2. 0445110457 Injector's Common Part Number	2
1.3.0445110457 Injector's Matching Information	
1.4.0445110457 Injector's Parameter	
1.5.0445110457 Injector's Specifications and Dimensions	
1.6. 0445110457 Injector's Quality Control	
1.7. 0445110457 Injector's Customized Service	6
1.8.0445110457 Injector's Packing and Package Size	6
1.9.0445110457 Injector's Testing Standard and Certificate	
1.10.0445110457 Injector's Warranty Instructions	8
1.11.0445110457 Injector's Manufacturer	
2.0445110457 Injector Technical Support	
2.1.0445110457 Injector's Part Number Location	
2.2.0445110457 Injector's Application Scenarios	9
2.3.0445110457 Injector's Installation	
2.4. 0445110457 Injector 's Reasons for Not Working Normally	11
2.5. 0445110457 Injector 's Causes of Damage	11
2.6.0445110457 Injector's Technical Support Obtaining Methods	11
3.0445110457 Injector's Purchase and Delivery	
3.1.0445110457 Injector's Purchase Payment Term	12
3.2.0445110457 Injector's Main Sales Markets	12
3.3.0445110457 Injector's Declaration Requirements	12
3.4.0445110457 Injector's Shipping Ways	
3.5.0445110457 Injector's Lead time	12
3.6.0445110457 Injector's Logistics Time for Destination Out of China's Areas	
3.7.0445110457 Injector's Packing	
4.0445110457 Injector's Storage Standard	
5. Company Information	15
5.1. Company Introduction	15
5.2. Sales-men's Contact Information	16
6. Copyright Statement	

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

0445110457 Injector CRI2-16 Technical File

1.0445110457 Injector's Introduction

1.1. 0445110457 Injector's Basic Information

SUMPER	Title	super-	China made new high quality diesel injector 0445110457 fuel injector CRI2-16
AN/OF	SKU1	and the	ي المحلف المعصف المحلف المحلف المحلف المحلف المحلف المحلف المحلف الم
	SKU2		
110	"Mainter	100	ה "ארונה "ארונה "ארונה "אירה "ארונה "ארונה "ארונה "ארונה "א

1.2. 0445110457 Injector's Common Part Number

(1) Injector's Exchange Information

States and a state of the	Injector Part Number	Re-manufactured Part Number
	0445110457	0 986 435 254
with with	The The The The	and the set of the set

(2) Injector's Application Information

Injector Part Number	CASE Car Model	CASE NEW HOLLAND	IVECO	NEW HOLLAND	
0 445 110 457	580 147 00 98	5801470098	5801470098	5801470098	
0 986 435 254	580 147 00 98	5801470098	5801470098	W. Contra	11152 I.S.
0 960 435 254	900 - 900 - 900 - 900 - 900 - 900 - 900 - 900 - 900 - 900 - 900 - 900 - 900 - 900 - 900 - 900 - 900 - 900 - 900	5801470098R	100	38. 344	0 357

(3) Injector's Part Number Common Writing



1.3.0445110457 Injector's Matching Information

Vehicle brand	Series	Car Model	Engine Model	Production date	Power (KW)	emission standard	Horse power	Manufacturer	Emission	Cylinder	Power Source (V)
CASE		SR220	F5HFL413A	01/2013 - 12/2014	61 kW	83 PS	/	/	/	4	12

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

			amate			201) -				
CASE	SR250	F5HFL413A	07/2012 - 03/2016	67 kW	91 PS	/	/	/	4	12
CASE	SV250	F5HFL413A	01/2013 -	61 kW	83 PS	/	1	/	4	12
CASE	SV300	F5HFL413A	07/2012 -	67 kW	91 PS	/	1	/	4	12
CASE	SV300	F5H	09/2015 -	67 kW	90 PS	/	/	/	4	-
CASE	TR320	F5HFL413A	07/2012 - 09/2016	67 kW	91 PS	/	1	/	4	12
CASE	TV380	F5H	09/2015 -	66 kW	90 PS	/	/	/	4	-
CASE	TV380	F5HFL413A	07/2012 -	67 kW	91 PS	/	1	/	4	12
NEW HOLLAN D	C232	F5CE5454B	04/2011 -	56 kW	76 PS	/	/	/	4	12
NEW HOLLAN D	C238	F5CE5454B	04/2011 - 12/2013	62 kW	84 PS	/	/	/	4	12
NEW HOLLAN D	L230	F5HFL413A	07/2012 - 12/2015	62 kW	84 PS	/	1	/	4	12
NEW HOLLAN D	T4.100 F	F5DFL413K	03/2016	73 kW	99 PS	/	1	/	4	12
NEW HOLLAN D	T4.100 LP	F5DFL413K	05/2017 -	73 kW	99 PS	/	1	/	4	12
NEW HOLLAN D	T4.100 N	F5DFL413K	04/2017 -	73 kW	99 PS	/	/	/	4	12
NEW HOLLAN D	T4.100V	F5DFL413K	04/2017 -	73 kW	99 PS	/	/	/	4	12
NEW HOLLAN D	T4.105	F5DFL413	12/2012 -	79 kW	107 PS	/	/	/	4	12

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

		ienznen Si	lamatt	ICCIIII		JU., L	iu .			
NEW HOLLAN D	T4.110 F	F5DFL413J	03/2016 -	79 kW	107 PS	/	/	/	4	12
NEW HOLLAN D	T4.110 LP	F5DFL413J	05/2017 -	79 kW	107 PS	/	/	/	4	12
NEW HOLLAN D	T4.110 N	F5DFL413J	04/2017	79 kW	107 PS	/	/	/	4	12
NEW HOLLAN D	T4.110V	F5DFL413J	04/2017 -	79 kW	107 PS	/	/	/	4	12
NEW HOLLAN D	T4.115	F5DFL413	06/2013 - 10/2017	85 kW	116 PS	/	/	/	4	12
NEW HOLLAN D	T4.75	F5DFL413	06/2013 - 08/2017	55 kW	75 PS	/	/	/	4	12
NEW HOLLAN D	T4.80 F	F5DFL413	03/2016 -	55 kW	75 PS	/	1	/	4	12
NEW HOLLAN D	T4.80 LP	F5DFL413	05/2017 -	55 kW	75 PS	/	1	/	4	12
NEW HOLLAN D	T4.80 N	F5DFL413	04/2017 -	55 kW	75 PS	/	1	/	4	12
NEW HOLLAN D	T4.80V	F5DFL413	04/2017 -	55 kW	75 PS	/	1	/	4	12
NEW HOLLAN D	T4.85	F5DFL413	12/2012 -	63 kW	86 PS	/	/	/	4	12
NEW HOLLAN D	T4.90 F	F5DFL413L	03/2016 -	63 kW	86 PS	/	/	/	4	12
NEW HOLLAN D	T4.90 LP	F5DFL413L	05/2017 -	63 kW	86 PS	/	/	/	4	12
NEW HOLLAN D	T4.90 N	F5DFL413L	04/2017 -	63 kW	86 PS	/	/	/	4	12
NEW HOLLAN D	T4.90V	F5DFL413L	04/2017 -	63 kW	86 PS	/	/	/	4	12

Press, Press,

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

	_				•					
NEW HOLLAN D	T4.95	F5DFL413	12/2012 -	73 kW	99 PS	/	/	/	4	12
NEW HOLLAN D	T5.105	F5DFL413	07/2012 -	79 kW	107 PS	/	1	/	4	12
NEW HOLLAN D	T5.115	F5DFL413	07/2012 -	84 kW	114 PS	1	1	/	4	12
NEW HOLLAN D	T5.75	F5DFL413A	04/2017 -	55 kW	75 PS	/	/	/	4	12
NEW HOLLAN D	T5.85	F5DFL413L	04/2017 -	63 kW	86 PS	/	/	/	4	12
NEW HOLLAN D	T5.95	F5DFL413	01/2012 -	73 kW	99 PS	/	/	/	4	12
NEW HOLLAN D	TD5.10 5	F5DFL413H	10/2014 -	79 kW	107 PS	/	/	/	4	12
NEW HOLLAN D	TD5.11 5	F5DFL413H	10/2014 -	84 kW	114 PS	/	/	/	4	12
NEW HOLLAN D	TD5.85	F5DFL413H	10/2014 -	63 kW	86 PS	/	/	/	4	12
NEW HOLLAN D	TD5.95	F5DFL413H	10/2014 -	73 kW	99 PS	/	/	/	4	12

1.4.0445110457 Injector's Parameter

Adaptation System: Common Rail System Injector Series: 110 Series Parameter Performance: CRI2-16 Matching Accessories: F 00V C17 504, gasket Injector Type: Electromagnetic Injector Support System Maximum Pressure: 1600 Vehicle Configuration Information: CASE/CASE NEW HOLLAND/IVECO/NEW HOLLAND

1.5.0445110457 Injector's Specifications and Dimensions Injector Size: 21.5cm*4 cm *4 cm = 344cm³ (L*W*H=V) Injector Net Weight: 0.55kg

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

Gross Weight: 0.6kg

Injector Quality: China Made Brand New Package Size: 28cm*7 cm *7 cm = 1372 cm³ Injector Type: Diesel Common Rail Injector MOQ: 4 Pieces

1.6. 0445110457 Injector's Quality Control

(1) Injector Testing

All injector spare parts are tested for electrical characteristics, accuracy, high temperature, low temperature, withstand voltage, leakage, durability, and various working conditions.

(2) Injector Assembling

And the quality control of the injector production and installation process, our company strictly follows the standard product installation data and product installation steps to install, such as injector stroke test, injector solenoid valve tightening torque, injector nozzle tightening torque,

(3) Injector Inspection

The factory inspection of the injector is undergone full inspection, random inspection, and batch inspection three inspections. Different brands of test benches are used to test the same fuel injector for a total of no less than three times for factory inspection, and the fuel injector installation testing environment are progressed in dust-free workshop.

1.7. 0445110457 Injector's Customized Service

(1) Injector's Customized Service: Meet the customized needs of OEM manufacturers for shell lettering, logo engraving, injector internal packaging, injector external packaging and labels customized, etc.



(2) Injector's Customized Service Requirements:

The purchased of customized injector are not less than 10 pieces.

Customized injector packages no less than 1000 pieces.

Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file.

A Once the customized fuel injector is sold, it cannot be returned or exchanged if there is no quality problems.

1.8.0445110457 Injector's Packing and Package Size

(1) Injector Spare Parts List

No.		2	3
Image		1	0
Name	Fuel Injector	O-Ring	Gasket F 00V C17 503

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

Description	Fuel injector part number: 0445110457	Ensure to meet the standard of the sealing performance between the injector and the engine	Made of brass, used to ensure the tight fit between the injector cap end and the engine		
No.	4	5	6		
Image					
Name	Nozzle Protective Cover Cap	Injector House Protective Cover Cap	Solenoid Valve Protective Cap		
Description	Protect nozzle holes from being polluted and blocked	Protect oil inlet from being polluted and blocked	Protect the solenoid valve body and terminals from being damaged by external forces		
No.	7	8	9		
Image					
Name	VCI Anti-rust Bag	Bubble Bag	Injector Packing Box		
Description	Prevent fuel injector from rusting	Prevent the injector from being damaged by external forces	Place injector and injector accessories		

▲ Minors are forbidden to use the fuel injector assembly, O-ring, gasket, nozzle protective cover, fuel injector house protective cover, solenoid valve protective cover, VCI anti-rust bag, and air bubble bag to avoid personal injury.


▲ O-ring and gasket are disposable installation accessories, and need to be replaced for

re-installation.

▲ The nozzle protective cover, the injector house protective cover, and the solenoid valve protective cover are recyclable accessories that can be reused.

▲ VCI anti-rust bags and bubble bags are non-degradable materials, please dispose of them properly after using.

▲ The injector and the installation parts should be coated with appropriate sealing oil during installation.



(2) Injector Box Size

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

5	HUMATT	Shenzhen Shumatt Technology Co., Ltd	
			_

No.	Name	Injector Package Size (cm)
1	Injector Box	28*7*7

1.9.0445110457 Injector's Testing Standard and Certificate

We can provide the factory quality inspection test report of each injector to ensure that each injector delivered meets the engine performance indicators.

BOTEN		测试	服告	4.05.2019	10:42:05
录争企业:					
Q12:		201	t;		
() 耳:		422	8人:		
SCHEME:					
tið:			8单位:		
传真:		谢)	¹ 胜名:		
秋季说道:					
2211名标:	micos				
型号-零件号:					
hina.					
		檢測	結果		
0198819-0					
	喻新药消费数	946218	FORM OF 9	REALESS FOR	
LEAR TEST:	3.8	· · · · ·		3022148	~
Radi:	32	+	75.7	AL 0 4 21 4	*
WARM	x.	147 3 ±16 5	c>	·····	
Max:	2015	218 5=14.4	63	and Bernet	~
TL:	28.4	346285		1	4
102	14.1	122248	e >		* *
VP;	10	41-12	0	•	1
(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	2 24 25 推注标	THE	THE STATE OF		



1.10.0445110457 Injector's Warranty Instructions

(1) . Product Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the injector inspection equipment when the injector is abnormal during use as evidence to feed back to the salesman.

Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting the engine, 4. Engine noise, 5. oil leakage etc.

(2) . Injector Warranty Coverage

Within 15 days after customer receives the 0445110457 injector, if there is a performance failure and the product has no appearance damage, customer can choose to replace it or repair it;

If the 0445110457 injector has performance problems during the warranty period (3 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

If the injector house has obvious scratches, it can only be repaired and it will be returned as it is if the product is confirmed to be fault-free.

Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 months from the date of repairing.

(3) . Injector Out of Warranty Coverage

The warranty period has expired.

Injector failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, earthquake, and used in abnormal environment.

Customer disassembles or repairs the injector personally resulting in damage to the injector.

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

Injector damage caused by man-made reasons (throwing, strong magnetic field magnetization, set fire). Injector failure or injector damage caused by non-injector design, technology, manufacturing, quality and other issues.

Injector failure due to system pressure exceeding system approved pressure.

Injector failure caused by system voltage exceeding approved voltage.

Injector failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in the system fuel exceeding the standard requirements.

Injector failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).

Injector failure caused by not following the installation angle specified in the vehicle engine maintenance manual.

Injector failure caused by not following the cleaning requirements specified in the vehicle engine maintenance manual.

Injector failure caused by failure to replace consumable parts as specified in the vehicle engine maintenance manual.

Injector failure caused by not complying with the intake system fit clearance and exhaust system fit clearance requirements specified in the vehicle engine maintenance manual.

Failure to replace the consumable parts and the fitting clearance of the oil inlet system pipeline and the fuel injector connection in accordance with the fuel intake system specified in the vehicle engine maintenance manual.

1.11.0445110457 Injector's Manufacturer

Injector's manufacturer: Shenzhen Shumatt Technology Co., Ltd

2.0445110457 Injector Technical Support

2.1.0445110457 Injector's Part Number Location


1) E.g.: The injector part number see as follows



No.	Name
Α	brand, logo, part number, series number
B	nozzle part number

2.2.0445110457 Injector's Application Scenarios

Common rail system is an oil supply method refers to the diesel oil from the fuel tank sucked out by the gear pump through the oil-water separator and the gear pump to diesel fine filter, high-pressure pump, common rail pipe, and fuel injector, all together with the closed-loop fuel supply system composed of sensors and ECU that completely separates the generation of injection pressure and the injection process from each other.



							and here and have
No.	Name	No.	Name	No.	Name	No.	Name
1	Tank	5	Common Rail Pressure Sensor	9	Engine Crankshaft Sensor	A	High Pressure Oil Circuit
2	Diesel Filter	6	Common Rail Pipe	10	Camshaft Sensor	В	Low Pressure Oil Circuit
3	High-Pressure Pump	7	Injector	11	ECU Electronic Control Unit	and a	96. M
4	Fuel Gear Pump	8	Accelerator Pedal		200 - 200 - 223		and the second

2.3.0445110457 Injector's Installation

SHUMAT

(1) .0445110457 Injector's Installation Precautions:

▲ The replacement of the fuel injector must strictly follow the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter and the high-pressure fuel circuit) specified in the vehicle engine maintenance manual,

▲ Replacement of wearing parts of the fuel system, cleaning requirements for the connection between the fuel system and the injector, the fitting clearance of the fuel injector connection, the installation angle and tightening torque of the injector, the fitting clearance of the intake system, and the fitting clearance of the exhaust system to ensure the service life of the engine and the normal operation of the injector.

▲ When installing the fuel injector on the engine, it is necessary to clean the engine block, cylinder head and other parts connected to the fuel injector, and ensure that there is no dust, carbon deposits, water, rust spots, etc.

▲ Before installing, check whether the fuel injector nozzle gasket has been replaced and installed on the fuel injector.

When installing the fuel injector, apply lubricant between the fuel injector, fuel nozzle sealing gasket and O-ring.

▲ Without replacing new gasket can lead to: deformation of the tight cap of nozzle, deformation of nozzle, deformation of nozzle orifice, oil leakage and air leakage, which will cause serious damage to the fuel injector and nozzle to break and cause damage to the engine.

When installing the injector on the engine, please carefully check the components related to the installation of the injector, such as the injector pressure plate, screw, injector rod and other accessories are not deformed, and install it in strict accordance with the operation steps of the engine maintenance manual.
It is forbidden to operate the bare injector for a long time in an environment with serious dust pollution and corrosion to iron products.

It is forbidden to operate the bare injector for a long time in a strong magnetic field environment.

2.4. 0445110457 **Injector 's Reasons for Not Working Normally**

(1) There is air in the oil circuit of the engine fuel system.

(2) Vehicle oil pump oil supply system is not normal.

(3) Engine common rail system oil leakage or pressure limiting valve damage.

(4) There is a short circuit, cutting out and poor contact in the wiring harness connected to the fuel injector of the vehicle.

(5) The long-term placement of the injector causes the anti-rust oil to solidify, and the internal components are stuck or the oil holes are blocked.

▲ Before installing, carefully check whether other components in the common rail system except the fuel injector are damaged so as to prevent the fuel injector from not working properly after being replaced.

2.5. 0445110457 Injector 's Causes of Damage

(1) Didn't operate properly according to engine maintenance manual during disassembly or installation, resulting in damage to the injector .

(2) The fuel oil used for the vehicle does not meet the standard cause damage to the injector, such as: the water content in the fuel oil exceeds the standard, iron powder, aluminum powder, sulfide impurities exceed the standard, etc.

(3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating oil of the engine system for a long time will cause abnormal wear of the engine, excessive exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced during maintenance or the replaced filter cannot reach the original filter standard. all above reasons can cause damage to the injector.

(4) The abrasion of the oil pump produces iron powder and aluminum powder enter the fuel injector and cause damage to the fuel injector.

(5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the fuel injector and causing damage to the fuel injector.

(6) The fuel injector is damaged due to replacement or adjustment of the relevant parts of the fuel injector. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the injector fails to meet the original standard.

(7) The engine is overheated and overloaded for a long time working results in damage to the fuel injector.

(8) The injector will be damaged naturally at the end of its working life.

(9) The injector is magnetized (injector parts' magnetic exceeded) causing the injector to not work properly.
A Before replacing the fuel injector, please check the engine parts carefully according to the engine maintenance manual to avoid the fuel injector being damaged again after replacement.

2.6.0445110457 Injector's Technical Support Obtaining Methods

(1) Injector Technical File, visit <u>http://shumatt.com</u> to get the technical file.

(2) Injector Technical Videos

Facebook: Visit <u>https://www.facebook.com/hison.li</u> to get the technical videos, constantly follow can get more information.

YouTube: <u>https://www.youtube.com/channel/UCByvYBx7VjV_mAfxh_Hu-aw</u> to get the technical videos, constantly follow can get more information.

Shumatt: Visit <u>http://shumatt.com</u> to get the technical videos.

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

(3) Injector Information Query Software

TruckBook Parts EPC APP, Android/Apple App Store download and install, visit <u>http://shumatt.com</u> to get the download and installation tutorial

(4) Search The fuel injector test data through TruckBook Parts EPC APP.

3.0445110457 Injector's Purchase and Delivery

3.1.0445110457 Injector's Purchase Payment Term

Payment Terms: T/T, PayPal, Alipay, WeChat

Please contact our salesmen for specific payment information.

3.2.0445110457 Injector's Main Sales Markets

Injector main sales markets: Asia, Europe, North America, South America, Africa etc.

3.3.0445110457 Injector's Declaration Requirements

Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

3.4.0445110457 Injector's Shipping Ways

Destination in China areas: SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

Destinations out of China's areas: DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

3.5.0445110457 Injector's Lead time

Lead time: Send out within 3 - 7 working days after receiving payment (Except for special products and special cases).

3.6.0445110457 Injector's Logistics Time for Destination Out of China's Areas

DHL Logistics Time :

Country or Region of Departure	Hong Kong, China	Other Countries or Regions of Asia	Australia and New Zealand	Europe	America	Other Countries
China's Mainland	7 Days	7 Days	8 Days	8 Days	8-12 Days	7-10 Days

UPS Logistics Time: Country or Region of Departure: China's Mainland

Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time
Japan	3 Days	UK	5-7Days	Egypt	5-7 Days
Turkey	5-7 Days	Singapore	3 Days	Switzerland	5-7 Days
Bahrain	5-7 Days	Latvia	7-10 Days	New Zealand	7-10 Days
Sri Lanka	5-7 Days	Thailand	3 Days	Austria	5-7 Days
Romania	5-7 Days	Vietnam	3-5 Days	Estonia	5-7 Days
Malaysia	3-5 Days	Israel	5-7 Days	Mexico	7-10 Days
France	5-7 Days	America	5-7 Days	United Arab Emirates	5-7 Days
Italy	5-7 Days	Netherlands	5-7 Days	Bengal	7-10 Days

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

<u>sjiuiin</u>		nzhen Shumat		CO., Ltu	
Lebanon	5-7 Days	Philippine	3-5 Days	Greece	7-10 Days
South Korea	3 Days	Spain	5-7 Days	Myanmar	5-7 Days
Canada	5-7 Days	Germany	5-7 Days	Saudi Arabia	7-10 Days
Portugal	5-7 Days	Australia	5-7 Days	South Africa	7-10 Days
Denmark	5-7 Days	Belgium	5-7 Days	Ukraine	7-10 Days
India	7-10 Days	Qatar	7-10 Days	Poland	5-7 Days
Indonesia	3-5 Days	Morocco	7-10 Days	Pakistan	7-10 Days
Kuwait	7-10 Days	al at a	i materia	Sec. St.	at and

The logistics time is for reference only, subjects are according to the actual arrival.

3.7.0445110457 Injector's Packing

Domestic express packaging: Usually wrapped in waterproof scotch tape, such as picture No.2.

International express packaging: Wrapped with waterproof yellow tape After wrapping the black protective film, such as picture No. 3.

Pallet Shipping: Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 4,

also, the products can be packaged according to customers' requirements.

- ▲ The packing tray is made of plastic and can be recycled.
- Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are non-degradable materials, please dispose of them properly.

Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury.



Pic No. 2 Domestic express packaging: Wrapped with Transparent tape



International express packaging: Wrapped with yellow tape after wrapping black protective film

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd



Pic No. 4

Pallet Shipping: Use pallet that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties

4.0445110457 Injector's Storage Standard

(1) Choose a suitable storage place

The warehouse and cargo yard where the fuel injector is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acid, alkali, salt and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir area dry.

(2) Strict requirements of warehousing

Strict inspections should be carried out when the fuel injectors are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ash and other dirt, remove the rust and do antirust treatment in time. Packaged injectors must be protected from damage.

(3) Keep the warehouse dry and preventing moisture

The relative humidity is usually below 70% for the fuel injectors placed in the room, and the corrosion of the fuel injectors is significantly reduced.

Injectors must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

(4) Stack Properly

After the injector is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse

If the fuel injector package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.

A It is forbidden to leave the injector exposed in the air for a long time.

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

It is forbidden to store acid, alkali, salt and other substances together with the injector.

The unpacked fuel injector must be rust-proof during secondary storage.

5. Company Information



5.1. Company Introduction Chinese Name: 深圳市舒马特科技有限公司 English Name: Shenzhen Shumatt Technology Co., Ltd

Mob Phone/WeChat: +86-13410541523

HK Telephone: +852-67653519

Telephone: +86-755-23215133

Email: ruby@shumatt.com

Website: www.shumatt.net

Shenzhen Office: 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

Shenzhen Office: Room 428-430, Building B, Huafeng Zhigu Technology Industrial Park, Exit B, Fuyong Metro Station, Bao'an District, Shenzhen, China's Mainland

The The The The The Con The The The The The

Hong Kong Office: Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd

After-sales Service Address: Please contact our salesmen to obtain and provide the corresponding product maintenance reasons (Reference: <u>1.10.0445110457</u> Injector Warranty Instructions)

No.	Name	WeChat/WhatsApp	Email	Facebook	YouTube
1	Ruby	+86-13410541523	ruby@shumatt.com	Hison Li	Hison Li
2	lvy	+86-18025299821	sales@shumatt.com	Ivy Shumatt	Shumatt IVY
3	Rebecca	+86-18025349821	sales01@shumatt.com	Rebecca SHUMATT	SHUMATT Rebecca
4	Janny	+86-18028749821	sales02@shumatt.com	Janny shumatt	Janny Shumatt
5	Sam	+86-13316859821	Sales8@shumatt.com	Shumatt Sam	Sam Shumatt
6	Natalie	+86- 18938945856	sales15@shumatt.com	Shumatt Natalie	Lin Natalie
7	Ada	+86-1342286353	sales5@shumatt.com	Shumatt Ada	Ada Shumatt
8	Hison Li	+86-18318811871	web@shumatt.com	Hison Li	Hison Li
9	Mecca	+86-18938948618	sales11@shumatt.com	Shumatt Mecca	Shumatt Mecca
10	Eric	+86 18319033618	sales3@shumatt.com		1.5
11	Wayne (Joaquín en español)	+86-13316959821	wayne@shumatt.com	shumattwayne	Wayne Shumatt
12	Sylvia	+86 18312499884	sales6@shumatt.com	Str. She	100 - 100 -
		visit http://shumatt.com to ob	tain the latest information of sales-	men	
		PS: Shumatt's sales-men's er	mails are all end with @shumatt.co	om	Sal 1540

5.2. Sales-men's Contact Information

6. Copyright Statement

The copyright of any contents (including but not limited to parameters, data, text, charts, images, sounds or videos, etc.) provided in "0445110457 *Injector* CRI2-16 *Technical File*" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "0445110457 *Injector* CRI2-16 *Technical File*" in any way. At the same time, any conditions to spread, re-post, display the contents of "0445110457 *Injector* CRI2-16*Technical File*" in any way. At the same time, any conditions to spread, re-post, display the contents of "0445110457 *Injector* CRI2-16*Technical File*" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "0445110457 *Injector* CRI2-16 *Technical File*" will violate the "*Copyright Law of the People's Republic of China*" and other laws and regulations and the provisions of relevant international conventions.

Mob/WhatsApp: +86 13410541523 Email : <u>ruby@shumatt.com</u> © 2022 Shenzhen Shumatt Technology Co., Ltd