

# 0445120404 Injector CRIN2-16-BL Technical File

SKU: G1W20445120404









# 0445120404 Injector CRIN2-16-BL Technical File

### Content

0445120404 Injector CRIN2-16-BL Technical File	3
1. 0445120404 Injector's Introduction	3
1.1.0445120404 Injector's Basic Information	34.3 3
1.2.0445120404 Injector's Common Part Number	3
1.3.0445120404 Injector's Matching Information	4
1.2.0445120404 Injector's Common Part Number	94.5
1.5.0445120404 Injector's Specifications and Dimensions	5
1.6. 0445120404 Injector's Quality Control	
1.7. 0445120404 Injector's Customized Service	
1.8.0445120404 Injector's Packing List and Package Size	
1.9.0445120404 Injector's Testing Standard and Certificate	
1.10.0445120404 Injector's Warranty Instructions	
1.10.0445120404 Injector's Manufacturer	/
1.11.0445120404 Injector's Manufacturer	c
2.1.0445120404 Injector Technical Support	2
2.1.0445120404 Injector's Part Number Location	
2.2.0445120404 Injector's Application Scenarios	8
2.3.0445120404 Injector's Installation	
2.4.0445120404 Injector's Reasons for Not Working Normally	S
2.5.0445120404 Injector's Causes of Damage	10
2.6.0445120404 Injector's Technical Support Obtaining Methods	10
3.0445120404 Injector's Purchase and Delivery	. 10
3.1.0445120404 Injector's Purchase Payment Terms	. 10
3.2.0445120404 Injector's Main Sales Markets	. 11
3.3.0445120404 Injector's Declaration Requirements	. 11
3.4.0445120404 Injector's Shipping Ways	. 11
3.3.0445120404 Injector's Declaration Requirements 3.4.0445120404 Injector's Shipping Ways 3.5.0445120404 Injector's Lead time	. 11
3.6.0445120404 Injector's Logistics Time for Destination Out of China's Areas	. 11
3 7 0445120404 Injector's Packing	1.1
3.7.0445120404 Injector's Packing	12
5. Company Information	13
5. Company Introduction	1.0
5.1. Company Introduction	13
6. Copyright Statement	
Partings Artifaction through	ş
THINKLE THINKLE THE WALL	
the	ş#
SANDAL	
age, age, age, age, age, age, age, age,	sil <sup>8</sup>
SHARL	
Show Show Show Show Show Show Show Show	giệ
THE SHORT OF THE LEAST SHELL S	
days. Mar. days. days. days. days. days., days., days., days., days., days., days., days.,	98
THE	

Mob/WhatsApp: +86 13410541523 Email: <a href="mailto:ruby@shumatt.com">ruby@shumatt.com</a>

© 2022 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133



### 0445120404 Injector CRIN2-16-BL Technical File

SHIPSILL PHISSILL PHISSILL

# 1. 0445120404 Injector's Introduction

1.1.0445120404 Injector's Basic Information

23,67	Title	- St. 100	89,000	China ma	de new	high qual	ity diese	l injector	0445120	404	31/07	-50
	SKU					G1W20	4451204	104				
6.92	6 . di	4. a. a.	500 200	10 mag 1	40000	10000	4.45	1.4000	1.000	4.005	~ 00°	C) .

# 1.2.0445120404 Injector's Common Part Number (1) Injector's Fychange Information

### (1) Injector's Exchange Information

	Inje	ector Pa	rt Num	ber	Re-mar	nufacture	d Part N	umber	
30.	34	. 99		94	- 50	30.	. 34.,	30	34.
		044512	20404				,		
	-47 S	100	100		3	-50°	- 17 Page 1	Sept 1	- CO

### (2) Injector's Application Information

Injector Part Number	/	/	/	/
044532040433		-d / -d	at	/ /
0445120404	and the state of		' 45 C	A STORY

# (3) Injector's Part Number Common Writing

0445120404, 0 445 120 404, 0445 120 404, 0445120 404, 0 445120404, 0 445120 404

80 <sup>(6)</sup>
90 <sup>85</sup>
93(8)
50 <sup>65</sup>
50 <sup>50</sup>
gh <sup>gg</sup>
9) <sup>(8)</sup>
50 <sup>(5)</sup>
91 <sup>34</sup>

Mob/WhatsApp: +86 13410541523 Email: ruby@shumatt.com

© 2022 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133 Website: www.shumatt.com



1.3.0445120404 Injector's Matching Information

Vehicle Brand	Series	Car Model	Engine Model	Production Date	Power (KW)	Horse Power	Emission Standards	Manufacturer	Emissions (L)	Cylinder	Power Source (V)
	9	ANDER SANDER	Andrew Angles		sterios st	S18388	279,200	Stranger Stranger St.	# <u>#</u>		

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133
Email: ruby@shumatt.com Website: www.shumat

© 2022 Shenzhen Shumatt Technology Co., Ltd

Website: www.shumatt.com

### **1.4.0445120404** Injector's Parameter

Adaptation System: Common Rail System

Injector Series: 120 Series

Parameter Performance: CRIN2-16

Matching Accessories: Gasket F 00R J01 453 (15.1\*7.7\*1.5cm Without Groove)

Injector Type: Electromagnetic Injector
Support System Maximum Pressure: 1,600

Vehicle Configuration Information:

### 1.5.0445120404 Injector's Specifications and Dimensions

Injector Size:  $21 \text{ cm}^*7 \text{ cm}^*6 \text{ cm} = 882 \text{ cm}^3 (L^*W^*H=V)$ 

**Injector Net Weight:** 0.45kg

Gross Weight: 0.6kg

Injector Quality: China Made Brand New Injector
Package Size: 28cm\*7 cm \*7 cm = 1372 cm³
Injector Type: Diesel Common Rail Injector

MOQ: 4 Pieces

### 1.6. 0445120404 Injector's Quality Control

### (1) Injector Testing

All injector spare parts are tested for electrical characteristics, accuracy, high temperature, low temperature, withstand voltage, leakage, durability, and various working conditions.

### (2) Injector Assembling

And the quality control of the injector production and installation process, our company strictly follows the standard product installation data and product installation steps to install, such as injector stroke test, injector solenoid valve tightening torque, injector nozzle tightening torque,

### (3) Injector Inspection

The factory inspection of the injector is undergone full inspection, random inspection, and batch inspection three inspections. Different brands of test benches are used to test the same fuel injector for a total of no less than three times for factory inspection, and the fuel injector installation and test environment are progressed in dust-free workshop.


### 1.7. 0445120404 Injector's Customized Service

(1) Injector's Customized Service: Meet the customized needs of OEM manufacturers for shell lettering, logo engraving, injector internal packaging, injector external packaging and labels customized, etc.



Injector nozzle engraving





### (2) Injector's Customized Service Requirements:

The purchased of customized injector are not less than 10 pieces.

Customized injector packages no less than 1000 pieces.

Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file.

▲ Once the customized fuel injector is sold, it cannot be returned or exchanged if there is no quality problems.

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133
Email: ruby@shumatt.com Website: www.shumatt.com



### 1.8.0445120404 Injector's Packing List and Package Size

(1) Injector Spare Parts List

								-007	- C		
No.	Real Philipses	1,500	283500	18 Jan 19 19 19 19 19 19 19 19 19 19 19 19 19	2	2000	- 20		3	300	1
limage				S. C. S.			1 3 3 1	ON TO SHAPE			31) 51)
Name	Fue	l Injector	1000	-10 March	O-Rii	ng	er Later	Gasl	ket F 00V C1	7 503	200
Description	Fuel injector part	sealing p	o meet the serformance	between t		Made of brass, used to ensure the tight fit between the injector cap end and the engine					
No.	200	4	517	970,500	91 <sup>0,0</sup> 5	500,000	97/2	50,000	6	200	90
ST Image	50° (		Sec.	<sup>SI</sup> FJ			STA	DELL.	(8)	j <sup>e</sup>	(1) (3) (4)
SHIMELL SH	J <sup>RP</sup>	550°	Store Store	st <sup>ell</sup>	SHIP.	SHIP.	1 100 PM	inger.	1000	100 m	(1) (1)
Name	Nozzle Prot	ective Cove	r Cap	Injecto	r Inlet Hole	Protective (	Cover	Injector Oi	Return Hole P	rotective Co	over
Description	Protect nozzle hol being polluted an	to the same of	TT		he injector i lluted and b		om	200	injector oil retued	K 70.	m <sub>-</sub>
No.	-340	7	\$1500m	27	8	200	-0.0	27	9	2700	\$30
St Image	TO THE SECOND SE	No.   No.		Sl <sup>8,18</sup>			99, 1	S (		007	50 <sup>6</sup>
	JEEF LEDWIN	- 18 P	_00.000°	202	- 100 m	- 20	ا المارية	OF SHAPE	2000	- 10 pt	
Name		nti-rust Bag			Bubble		1077	F	njector Packing	Box	
Description	Prevent fuel inject rusting	tor from	55		the injector I by externa	_	gG <sup>3</sup>	Place inject	or and injector	accessories	855
1555	1970	. 2000						FT - FT	70 - F770 1	1.000	

Minors are forbidden to use the fuel injector assembly, O-ring, gasket, nozzle protective cover, fuel injector house protective cover, solenoid valve protective cover, VCI anti-rust bag, and air bubble bag to avoid personal injury.

▲ O-ring and gasket are disposable installation accessories, and need to be replaced for re-installation.

▲ The nozzle protective cover, the injector house protective cover, and the solenoid valve protective cover are recyclable accessories that can be reused.

**A** VCI anti-rust bags and bubble bags are non-degradable materials, please dispose of them properly after using.

▲ The injector and the installation parts should be coated with appropriate sealing oil during installation.



Mob/WhatsApp: +86 13410541523


Email: <a href="mailto:ruby@shumatt.com">ruby@shumatt.com</a>

© 2022 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133 Website: www.shumatt.com



### (2) Injector Box Size



### 1.9.0445120404 Injector's Testing Standard and Certificate

We can provide the factory quality inspection test report of each injector to ensure that each injector delivered meets the engine performance indicators.



### 1.10.0445120404 Injector's Warranty Instructions

### (1) . Product Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the injector inspection equipment when the injector is abnormal during use as evidence to feed back to the salesman.

Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting the engine, 4. Engine noise, 5. oil leakage etc.

### (2) . Injector Warranty Coverage

Within 15 days after customer receives the **0445120219** injector, if there is a performance failure and the product has no appearance damage, customer can choose to replace it or repair it;

If the **0445120219** injector has performance problems during the warranty period (3 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

Mob/WhatsApp: +86 13410541523

Email: ruby@shumatt.com

© 2022 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133

Website: www.shumatt.com

If the injector house has obvious scratches, it can only be repaired and it will be returned as it is if the product is confirmed to be fault-free.

▲ Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 months from the date of repairing.

# (3) . Injector Out of Warranty Coverage

The warranty period has expired.

Injector failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, earthquake, and used in abnormal environment.

Customer disassembles or repairs the injector personally resulting in damage to the injector.

Injector damage caused by man-made reasons (throwing, strong magnetic field magnetization, set fire).

Injector failure or injector damage caused by non-injector design, technology, manufacturing, quality and other issues.

Injector failure due to system pressure exceeding system approved pressure.

Injector failure caused by system voltage exceeding approved voltage.

Injector failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in the system fuel exceeding the standard requirements.

Injector failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).

Injector failure caused by not following the installation angle specified in the vehicle engine maintenance manual.

Injector failure caused by not following the cleaning requirements specified in the vehicle engine maintenance manual.

Injector failure caused by failure to replace consumable parts as specified in the vehicle engine maintenance manual.

Injector failure caused by not complying with the intake system fit clearance and exhaust system fit clearance requirements specified in the vehicle engine maintenance manual.

Failure to replace the consumable parts and the fitting clearance of the oil inlet system pipeline and the fuel injector connection in accordance with the fuel intake system specified in the vehicle engine maintenance manual.

### 1.11.0445120404 Injector's Manufacturer

Injector's manufacturer: Shenzhen Shumatt Technology Co., Ltd

### 2.0445120404 Injector Technical Support

### 2.1.0445120404 Injector's Part Number Location

1) E.g.: The injector part number see as follows




No.	Name						
The section of	brand, logo, part number,						
Signa Sign	series number						
В	nozzle part number						

### 2.2.0445120404 Injector's Application Scenarios

Common rail system is an oil supply method refers to the diesel oil from the fuel tank sucked out by the gear pump through the oil-water separator and the gear pump to diesel fine filter, high-pressure pump, common rail pipe, and fuel injector, all together with the closed-loop fuel supply system composed of sensors and ECU that completely separates the generation of injection pressure and the injection process

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133
Email: ruby@shumatt.com Website: www.shumatt.com

### from each other.



Pic No. 1

No.	Name	No.	Name	No.	Name	No.	Name
1	Tank	5	Common Rail Pressure Sensor	9	Engine Crankshaft Sensor	Α	High Pressure Oil Circuit
2	Diesel Filter	6.00	Common Rail Pipe	10	Camshaft Sensor	В	Low Pressure Oil Circuit
3	High-Pressure Pump	7	Injector	11	ECU Electronic ControlUnit		
4	Fuel Gear Pump	√ 8 <sub></sub>	Accelerator Pedal	100000	The state of the s	100 P. T.	entition and the same

### 2.3.0445120404 Injector's Installation

(1) .0445120404 Injector's Installation Precautions:

**The replacement of the fuel injector must strictly follow** the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter and the high-pressure fuel circuit) specified in the vehicle engine maintenance manual,

A Replacement of wearing parts of the fuel system, cleaning requirements for the connection between the fuel system and the injector, the fitting clearance of the fuel injector connection, the installation angle and tightening torque of the injector, the fitting clearance of the intake system, and the fitting clearance of the exhaust system to ensure the service life of the engine and the normal operation of the injector.

▲ When installing the fuel injector on the engine, it is necessary to clean the engine block, cylinder head and other parts connected to the fuel injector, and ensure that there is no dust, carbon deposits, water, rust spots, etc.

▲ Before installing, check whether the fuel injector nozzle gasket has been replaced and installed on the fuel injector.

▲ When installing the fuel injector, apply lubricant between the fuel injector, fuel nozzle sealing gasket and O-ring.

▲ Without replacing new gasket can lead to: deformation of the tight cap of nozzle, deformation of nozzle, deformation of nozzle orifice, oil leakage and air leakage, which will cause serious damage to the fuel injector and nozzle to break and cause damage to the engine.

A When installing the injector on the engine, please carefully check the components related to the installation of the injector, such as the injector pressure plate, screw, injector rod and other accessories are not deformed, and install it in strict accordance with the operation steps of the engine maintenance manual.

▲ It is forbidden to operate the bare injector for a long time in an environment with serious dust pollution and corrosion to iron products.

▲ It is forbidden to operate the bare injector for a long time in a strong magnetic field environment.

The The The The The The

### 2.4.0445120404 Injector's Reasons for Not Working Normally

- (1) There is air in the oil circuit of the engine fuel system.
- (2) Vehicle oil pump oil supply system is not normal.

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133
Email: ruby@shumatt.com Website: www.shumatt.com



- (3) Engine common rail system oil leakage or pressure limiting valve damage.
- (4) There is a short circuit, cutting out and poor contact in the wiring harness connected to the fuel Carlotter States, States, States, States, States, States, States, States, injector of the vehicle.
- (5) The long-term placement of the injector causes the anti-rust oil to solidify, and the internal components are stuck or the oil holes are blocked. - Mar Mar Mar
- ▲ Before installing, carefully check whether other components in the common rail system except the fuelinjector is damaged so as to prevent the fuel injector from not working properly after being replaced.

- 2.5.0445120404 Injector's Causes of Damage

  (1) Didn't operate properly according (1) Didn't operate properly according to engine maintenance manual during disassembly or installation, et Paris 100 Page . 1990 P. T. resulting in damage to the injector.
- (2) The fuel oil used for the vehicle does not meet the standard cause damage to the injector, such as: the water content in the fuel oil exceeds the standard, iron powder, aluminum powder, sulfide impurities 1000 TO exceed the standard, etc.
- (3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating oil of the engine system for a long time will cause abnormal wear of the engine, excessive exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced during maintenance or the replaced filter cannot reach the original filter standard, all above reasons can cause أ1967م. المحافظة المراس AND SELECTION OF CARLES OF AND PROPERTY. damage to the injector. adilli (1860)
- (4) The abrasion of the oil pump produces iron powder and aluminum powder enter the fuel injector and cause damage to the fuel injector.
- (5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the fuel injector and causing damage to the fuel injector.
- (6) The fuel injector is damaged due to replacement or adjustment of the relevant parts of the fuel injector. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the injector fails to meet the original The The The 77 mg 77m 77m 77m 77m 77m 77m standard.
- (7) The engine is overheated and overloaded for a long time working results in damage to the fuel injector.
- (8) The injector will be damaged naturally at the end of its working life.
- (9) The injector is magnetized (injector parts' magnetic exceeded) causing the injector to not work properly.
- A Before replacing the fuel injector, please check the engine parts carefully according to the engine maintenance manual to avoid the fuel injector being damaged again after replacement.

### 2.6.0445120404 Injector's Technical Support Obtaining Methods

- (1) Injector Technical File, visit <a href="http://shumatt.com">http://shumatt.com</a> to get the technical file.
- (2) Injector Technical Videos

Facebook: Visit https://www.facebook.com/hison.li to get the technical videos, constantly follow can get more information.

YouTube: https://www.youtube.com/channel/UCByvYBx7VjV mAfxh Hu-aw to get the technical videos, constantly follow can get more information.

**Shumatt:** Visit <a href="http://shumatt.com">http://shumatt.com</a> to get the technical videos.

(3) Injector Information Query Software

TruckBook Parts EPC APP, Android/Apple App Store download and install, visit http://shumatt.com to get the download and installation tutorial

450

1000

490

(4) Search The fuel injector test data through TruckBook Parts EPC APP.

### 3.0445120404 Injector's Purchase and Delivery

### 3.1.0445120404 Injector's Purchase Payment Terms

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133 Email: ruby@shumatt.com Website: www.shumatt.com

Salah Salah

**Payment Terms:** T/T, PayPal, Alipay, WeChat

Please contact our salesmen for specific payment information.

### 3.2.0445120404 Injector's Main Sales Markets

Injector main sales markets: Asia, Europe, North America, South America, Africa etc.

### 3.3.0445120404 Injector's Declaration Requirements

Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

### 3.4.0445120404 Injector's Shipping Ways

**Destination in China areas:** SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

**Destinations out of China's areas:** DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

### 3.5.0445120404 Injector's Lead time

**Lead time:** Send out within 3-7 working days after receiving payment (Except for special products and special cases).

### 3.6.0445120404 Injector's Logistics Time for Destination Out of China's Areas

### **DHL Logistics Time:**

Country or Region of Departure	Hong Kong, China	Other Countries or Regions of Asia	Australia and New Zealand	Europe	America	Other Countries
China's Mainland	7 Days	7 Days	8 Days	8 Days	8-12 Days	7-10 Days

UPS Logistics Time: Country or Region of Departure: China's Mainland

Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time
Japan	3 Days	UK	5-7 Days	Egypt	5-7 Days
Turkey	5-7 Days	Singapore	3 Days	Switzerland	5-7 Days
Bahrain	5-7 Days	Latvia	7-10 Days	New Zealand	7-10 Days
Sri Lanka	5-7 Days	Thailand	3 Days	Austria	5-7 Days
Romania	5-7 Days	Vietnam	3-5 Days	Estonia	5-7 Days
Malaysia	3-5 Days	Israel	5-7 Days	Mexico	7-10 Days
France	5-7 Days	America	5-7 Days	United Arab Emirates	5-7 Days
Italy	5-7 Days	Netherlands	5-7 Days	Bengal	7-10 Days
Lebanon	5-7 Days	Philippine	3-5 Days	Greece	7-10 Days
South Korea	3 Days	Spain	5-7 Days	Myanmar	5-7 Days
Canada	5-7 Days	Germany	5-7 Days	Saudi Arabia	7-10 Days
Portugal	5-7 Days	Australia	5-7 Days	South Africa	7-10 Days
Denmark	5-7 Days	Belgium	5-7 Days	Ukraine	7-10 Days
India	7-10 Days	Qatar	7-10 Days	Poland	5-7 Days
Indonesia	3-5 Days	Morocco	7-10 Days	Pakistan	7-10 Days
Kuwait	7-10 Days	Think Think Think	in This		777 m

The logistics time is for reference only, subjects are according to the actual arrival.

### 3.7.0445120404 Injector's Packing

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133
Email: ruby@shumatt.com Website: www.shumatt.com



Domestic express packaging: Usually wrapped in waterproof scotch tape, such as picture No.2.

**International express packaging:** Wrapped with waterproof yellow tape After wrapping the black protective film, such as picture No. 3.

**Pallet Shipping:** Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 4, Also, the products can be packaged according to customers' requirements.

▲ The packing tray is made of plastic and can be recycled.

▲ Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are non degradable materials, please dispose of them properly.


▲ Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury.



Pic No. 2

Domestic express packaging:

Wrapped by Transparent tape
black protective film



International express packaging:
Wrapped with yellow tape after wrapping



Pic No. 4

**Pallet Shipping:** Use pallet that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties

### 4.0445120404 Injector's Storage Standard

### (1) Choose a suitable storage place

 $e^{-i\hbar \hat{J}^{(i)}}$ 

The warehouse and cargo yard where the fuel injector is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acids, alkalis, salts and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133
Email: ruby@shumatt.com Website: www.shumatt.com

area dry.

### (2) Strict requirements of warehousing

Strict inspections should be carried out when the fuel injectors are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ash and other dirt, remove the rust and do anti-rust treatment in time. Packaged injectors must be protected from damage.

### (3) Keep the warehouse dry and preventing moisture

The relative humidity is usually below 70% for the fuel injectors placed in the room, and the corrosion of the fuel injectors is significantly reduced.

Injectors must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

### (4) Stack Properly

After the injector is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse

If the fuel injector package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.

- It is forbidden to leave the injector exposed in the air for a long time.
- ▲ It is forbidden to store acids, alkalis, salts and other substances together with the injector.
- ▲ The unpacked fuel injector must be rust-proof during secondary storage.

# Office Locations Global Exhibitions

# 5.1. Company Introduction Chinese Name: 深圳市舒马特科技有限公司 English Name: Shenzhen Shumatt Technology Co., Ltd Mob Phone/WeChat: +86-13410541523 HK Telephone: +852-67653519 Telephone: +86-755-23215133 Email: ruby@shumatt.com Website: www.shumatt.net

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133
Email: ruby@shumatt.com Website: www.shumatt.com



Shenzhen Office: 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

Shenzhen Office: Room 428-430, Building B, Huafeng Zhigu Technology Industrial Park, Exit B, Fuyong Metro Station, Bao'an District, Shenzhen, China's Mainland

Hong Kong Office: Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

After-sales Service Address: Please contact our salesmen to obtain and provide the corresponding product maintenance reasons (Reference: 1.10.0445120404 Injector Warranty Instructions)

### 5.2. Sales-men's Contact Information

No.	Name	WeChat/ WhatsApp	Email	Facebook	YouTube
1,000	Ruby	+86-13410541523	ruby@shumatt.com	Hison Li	Hison Li
2	lvy	+86-18025309821	sales@shumatt.com	Ivy Shumatt	Shumatt IVY
3	Rebecca	Rebecca +86-18025349821 sales01@shur		Rebecca SHUMATT	SHUMATT Rebecca
4	Janny	+86-18028749821	sales02@shumatt.com	Janny shumatt	Janny Shumatt
5	Sam	+86-13316859821	Sales8@shumatt.com	Shumatt Sam	Sam Shumatt
6	Natalie	+86- 18938945856	sales15@shumatt.com	Shumatt Natalie	Lin Natalie
7	Ada	+86-1342286353	sales5@shumatt.com	Shumatt Ada	Ada Shumatt
8	Hison Li	Hison Li +86-18318811871		Hison Li	Hison Li
9	Mecca	+86-18938948618	sales11@shumatt.com	Shumatt Mecca	Shumatt Mecca
10	Erica -	+86 18319033618	sales3@shumatt.com	dd	S S
<b>11</b> 37000	Wayne ( Joaquín en español )	+86-13316959821	wayne@shumatt.com	shumattwayne	Wayne Shumatt
12	Sylvia	+86 18312499884	sales6@shumatt.com		
	20 20 20	Visit http://shumatt.com to ob	otain the latest information of salesmo	en i	d d
-35	The state of the s	PS: Shumatt's sales-men's e	mails are all end with @shumatt.com		100 July 100

### 6. Copyright Statement

The copyright of any contents (including but not limited to parameters, data, text, charts, images, sounds or videos, etc.) provided in "0445120404 Injector CRIN2-16-BL Technical File" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "0445120404 Injector CRIN2-16-BL Technical File" in any way. At the same time, any conditions to spread, re-post, display the contents of "0445120219 Injector CRIN2-16-BL Technical File" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "0445120404 Injector CRIN2-16-BLTechnical File" will violate the "Copyright Law of the People's Republic of China" and other laws and regulations and the provisions of relevant international conventions.

Mob/WhatsApp: +86 13410541523 Tel: +8675523215133
Email: ruby@shumatt.com Website: www.shumatt.com