

0445120332 Injector CRIN3-18 Technical File

SKU: G1W20445120332











0445120332 Injector CRIN3-18 Technical File SPARSE

L. Physical Physical

Content

0445	120332 In	jector CR	IN3-18 Te	chnical F	ile	-815	Ste.	Str	-832,	800	890	2
1.044	15120332	Injector's	Introduct	ion		es	e4	et		بير	ç	2ب
SH 1975	1.1.044512	20332 lnj	ector's Ba	sic Infor	mation.	4000	g0/5°	aght (SE	and the second			2
	1.2.044512	20332 Inj	ector's Co	mmon P	art Nun	nber						2
. p. 955	1.3.044512	20332 Inj	ector's M	atching I	nforma	tion	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	2
Silver	1.4.044512	20332 Inj	ector's Pa	rameter	450an	-810m	-38.f.o.,	S17**	83000	2777	2000	2
	1.5:044512	20332 Ini	ector's Sp	ecificatio	ons and	Dimensi	ions		ران <i>ې</i>	ç4g	ç4	, i 3
SINITE	1.6.044512	20332 Inj	ector's Qu	ality Co	ntrol	September 1						3
:	1.6.044512	20332 Inj	ector's Cu	stomize	d Servic	e						3
. 1, 100	1.7.044512	20332 Inj	ector's Pa	cking Lis	t and Pa	ackage Si	ze	S	Ti			<u>3</u>
	1.8.044512									Spine.	Ship.	5
:	1.9.044512	20332 <u>I</u> nj	ector's W	arranty I	nstructi	ons	ç4	çi	ç4	ç4	çış	بىتى 5
2.044	15120332	Injector T	echnical S	upport	ed for	98	ghi ^{gh}		-64500°			6
	2.1.044512											6
. 6.954	2.2.044512	20332 Inj	ector's Ap	plication	n Scenai	rios		T	Ti	<u> </u>	T	6
1571 ·	2.3.044512	20332 Inj	ector's In	stallation)	-945-	- 55	- 55"	-84	577	87"	7
:	2.4.044512	20332 Inj	ector's Re	asons fo	r Not W	orking N	Iormally					7 7
SH (170)	2.5.044512	20332 Inj	ector's Ca	uses of [Damage	- 1986 E.	<i>gb</i>			gg/////		
	2.6.044512											8
3.044	15120332	Injector's	Purchase	and Del	ivery			C	S			8
84	3.1.044512	20332 Inj	ector's Pu	rchase P	ayment	Terms	gw.	84	84	84	34	8
	3.2.044512										et	րե 8
SH _{TAGO}	3.3.044512	20332 Inj	ector's De	claratio	n Requii	rements					- 150°	8
3	3.4.044512	20332 Inj	ector's Sh	ipping W	/ays							9
دورون	3.5.044512	20332 Inj	ector's Le	ad time .								9
300	3.6.044512	20332 Inj	ector's Lo	gistics Ti	me for	Destinati	ion Out o	of China's	Areas	354	354.1	9
- 1	3.7.044512	20332 Inj	ector's Pa	cking		A	ρί	çü	, i	çû	çı	զդ 9
4.044	15120332	Injector's	Storage S	tandard	42.50°	- 616 Jan		64,700				10
5. Co	mpany Info	rmation	C			-5						
ا الارتيار	5.1 Compa	ny Introdu	ıction			in profile				التعويبيانا		11
en !	5.2. Salesm	en's Cont	act Inforn	nation	400	-0.0				1971	100	12
	pyright Stat					d	çi	çü	çi	çi	çü	
24,000	24/200	33/2700	Shippon	98,300	Sign	-2/6/2000	alisan	24/200	St. 1990	25/2700	29,200	318
				-4		d .					-t .	-41
enf 5 ⁵⁵		335	of the later		-01-100 PM	SPECION.	ri Sh ^{ush}	and state	37,575	1 July 1985	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	ro Lodo
QH1	DIT	Diri	pn			Gr h	gat h		041	D/1	pri	Oly.
. 100	5 ¹⁵ 5 ¹	S. Jack	Page 1	. vote Cal	September 1	n english	CI. STANSON	St. Land	S. Jack	O. Jan	San Park	ÇĞ.
Starting.	Shirm	831,000	81,300	200	SUPPLIED.	57(0.2554)	311	311/200	Shipper	81470	50,000	519
	ari ar	d sai	(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			g ja	d v	d.	d .	d	d	eri
- 400	Pri	100000	4600	4600	1000	1000	100000	1000	C	*	* 2000 P	-



0445120332 Injector CRIN3-18 Technical File

1.0445120332 Injector's Introduction

1.1.0445120332 Injector's Basic Information

104	Title		China m	ade new	/ high qu	ality diese	injector	044512	20332 C	RIN3-	18	200
	Jan 1971	200	200	200	20%	2007	200	200	200	25		45
3000 S	SKU	35 Street .	Service of	Salar.	all all the second	G1W2044	5120332	7. Sec	A Street	3,500	esta gira	-63

1.2.0445120332 Injector's Common Part Number

(1) Injector's Exchange Information

Injector Part Number	Re-manufactured Part Number
0445120332	SHORMEL SHORMEL PROPERTY.

(2) Injector's Application Information

Injector Part Number	CAMC Car Number	Car Number
0445120332	5 262	Show. Sho
0443120332	128	<i>L</i> -s
Strain, Strain	5/7/200	

(3) Injector's Part Number Common Writing

0445120332, 0 445 120 332, 0445 120 332, 0445120 332, 0 445120332, 0 445120 332

1.3.0445120332 Injector's Matching Information

Vehicle Brand	Series	Car Model	Engine Model	Production Date	Power (KW)	Horse Power	Emissio n Standar ds	Manufact urer	Emissio ns (L)	Cylin der	Power Source (V)
SHURDA	algraph, a	rates. Alexander	M. Staller	21/2/2024	Starings.	Stanton.	SHANDA	27,000	Sh. Son.	S. S. S. S.	24g
7800	77mm 2	- 1200 C	est Trans	77 m		300	i	inger in	i Para	ð.	1700

1.4.0445120332 Injector's Parameter

Adaptation System: Common Rail System

Injector Series: 120 Series

Parameter Performance: CRIN3-18

Matching Accessories: Gasket F 00R J02 175 (7.73*14.36*1.49)

 $\label{lem:mob_whatsapp: +86 13410541523 Tel: +8675523215133} \\ Email: \underline{ruby@shumatt.com} \\ Website: \underline{www.shumatt.com} \\$

Injector Type: Electromagnetic Injector Support System Maximum Pressure: 1,800 Vehicle Configuration Information: CUMMINS

1.5.0445120332 Injector's Specifications and Dimensions

Injector Size: 21.5cm*4 cm *4 cm = 344cm3 (L*W*H=V)

Injector Net Weight: 0.55kg

Gross Weight: 0.6kg

Injector Quality: China Made Brand New Injector Package Size: 28cm*7 cm *7 cm = 1372cm³ Injector Type: Diesel Common Rail Injector

MOQ: 4 Pieces

1.6.0445120332 Injector's Quality Control

(1) Injector Testing

All injector spare parts are tested for electrical characteristics, accuracy, high temperature, low temperature, withstand voltage, leakage, durability, and various working conditions.

(2) Injector Assembling

And the quality control of the injector production and installation process, our company strictly follows the standard product installation data and product installation steps to install, such as injector stroke test, injector solenoid valve tightening torque, injector nozzle tightening torque,

(3) Injector Inspection

The factory inspection of the injector is undergone full inspection, random inspection, and batch inspection three inspections. Different brands of test benches are used to test the same fuel injector for a total of no less than three times for factory inspection, and the fuel injector installation and test environment are progressed in dust-free workshop.

1.6.0445120332 Injector's Customized Service

(1) Injector's Customized Service: Meet the customized needs of OEM manufacturers for shell lettering, logo engraving, injector internal packaging, injector external packaging and labels customized, etc.





Injector shell lettering and QR code



Injector solenoid valve



Injector box and label

The purchased of customized injector are not less than 10 pieces.

Customized injector packages no less than 1000 pieces.

Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file. 20%

▲ Once the customized fuel injector is sold, it cannot be returned or exchanged if there is no quality problems.

1.7.0445120332 Injector's Packing List and Package Size

(1) Injector Spare Parts List

- 25	200	5/10	- 40	2-40	-27	- 20	A 201	4.00		~ (1)	2.70	
No.	1.00	1.403.7	46.3	440.0	467	- 4675	1 400	1000000	1,407,7	- 3	46.3	
1000	- 1000	- COST -	- 200	4000	4000	4.000	7.00	- 1000	- 4000		- 1000 h	

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133 Email: ruby@shumatt.comWebsite: www.shumatt.com



SHUMITT 深圳市舒马特科技有限公司

Shara Image		ATT SALT O SALTART	SWALL ON U.S. SWI.
Name	Fuel Injector	O-Ring	Gasket F 00R J02 175
Description	Fuel injector part number 0445120332	Ensure to meet the standard of the sealing performance between the injector and the engine	Made of brass, used to ensure the tight fit between the injector cap end and the engine
No.	4 41	ATT SHITT	SAME AND STREET
Image	gas all	Str. State	SWAME LE
Name	Nozzle Protective Cover Cap	Injector shell protective cover	Solenoid valve protective cover
Description	Protect nozzle holes from being polluted and blocked	Protect the injector inlet hole from being polluted and blocked	Protect the solenoid body and terminal posts from external forces
No.	7	. 8	. 9
Image			
No.	VCI Anti-rust Bag	Bubble Bag	Injector Packing Box
Image	Prevent fuel injector from rusting	Prevent the injector from being damaged by external forces	Place injector and injector accessories


A Minors are forbidden to use the fuel injector assembly, O-ring, gasket, nozzle protective cover, fuel injector house protective cover, solenoid valve protective cover, VCI anti-rust bag, and air bubble bag to avoid personal injury.

▲ O-ring and gasket are disposable installation accessories, and need to be replaced for re-installation.

▲ The nozzle protective cover, the injector house protective cover, and the solenoid valve protective cover are recyclable accessories that can be reused.

▲ VCI anti-rust bags and bubble bags are non-degradable materials, please dispose of them properly after using.

▲ The injector and the installation parts should be coated with appropriate sealing oil during installation.



Mob/Whatsapp: +86 13410541523 Tel: +8675523215133 Email: ruby@shumatt.comWebsite: www.shumatt.com



1 Injector Box

28*7*7

1.8.0445120332 Injector's Testing Standard and Certificate

We can provide the factory quality inspection test report of each injector to ensure that each injector delivered meets the engine performance indicators.



1.9.0445120332 Injector's Warranty Instructions

(1) . Product Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the injector inspection equipment when the injector is abnormal during use as evidence to feed back to the salesman.

Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting the engine, 4. Engine noise, 5. oil leakage etc.

(2) . Injector Warranty Coverage

Within 15 days after customer receives the **0445120332** injector, if there is a performance failure and the product has no appearance damage, customer can choose to replace it or repair it;

If the **0445120332** injector has performance problems during the warranty period (3 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

If the injector house has obvious scratches, it can only be repaired and it will be returned as it is if the product is confirmed to be fault-free.

▲ Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 months from the date of repairing.

(3) . Injector Out of Warranty Coverage

The warranty period has expired.

Injector failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, earthquake, and used in abnormal environment.

Customer disassembles or repairs the injector personally resulting in damage to the injector.

Injector damage caused by man-made reasons (throwing, strong magnetic field magnetization, set fire).

Injector failure or injector damage caused by non-injector design, technology, manufacturing, quality and other issues.

Injector failure due to system pressure exceeding system approved pressure.

Injector failure caused by system voltage exceeding approved voltage.

Injector failure caused by impurities (water, lead, aluminum powder, iron powder, sulfide) in the system fuel exceeding the standard requirements.

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133 Email: ruby@shumatt.comWebsite: www.shumatt.com

Injector failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (the tightening torque is too large or too small).

Injector failure caused by not following the installation angle specified in the vehicle engine maintenance manual.

Injector failure caused by not following the cleaning requirements specified in the vehicle engine maintenance manual.

Injector failure caused by failure to replace consumable parts as specified in the vehicle engine maintenance manual.

Injector failure caused by not complying with the intake system fit clearance and exhaust system fit clearance requirements specified in the vehicle engine maintenance manual.

Failure to replace the consumable parts and the fitting clearance of the oil inlet system pipeline and the fuel injector connection in accordance with the fuel intake system specified in the vehicle engine maintenance manual.

1.10.0445120332 Injector's Manufacturer

Injector's manufacturer: Shenzhen Shumatt Technology Co., Ltd

2.0445120332 Injector Technical Support

2.1.0445120332 Injector's Part Number Location


1) E.g.: The injector part number see as follows



No.	Name
-37° -37°	brand, logo, part number,
^	series number
B	nozzle part number

2.2.0445120332 Injector's Application Scenarios

Common rail system is an oil supply method refers to the diesel oil from the fuel tank sucked out by the gear pump through the oil-water separator and the gear pump to diesel fine filter, high-pressure pump, common rail pipe, and fuel injector, all together with the closed-loop fuel supply system composed of sensors and ECU that completely separates the generation of injection pressure and the injection process from each other.



Pic No. 1

No.	Name	No.	Name	No.	Name	No.	Name
-----	------	-----	------	-----	------	-----	------

 $\label{lem:mob_whatsapp: +86 13410541523 Tel: +8675523215133} \\ \text{Email:} \underline{\text{ruby@shumatt.com}} \\ \text{Website: } \underline{\text{www.shumatt.com}} \\$



1	Tank	5	Common Rail Pressure Sensor	9	Engine Crankshaft Sensor	А	High Pressure Oil Circuit
2,000	Diesel Filter	6,0	Common Rail Pipe	10	Camshaft Sensor	В	Low Pressure Oil Circuit
3	High-Pressure Pump	7	Injector	11	ECU Electronic Control Unit		1907 1 1907 1
4	Fuel Gear Pump	8	Accelerator Pedal	1	Charles Charles Co.	1000	Tiller Tiller

2.3.0445120332 Injector's Installation

(1) .0445120332 Injector's Installation Precautions:

The replacement of the fuel injector must strictly follow the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter 度 and the high-pressure fuel circuit) specified and the high-pressure fuel circuit)

A Replacement of wearing parts of the fuel system, cleaning requirements for the connection between the fuel system and the injector, the fitting clearance of the fuel injector connection, the installation angle and tightening torque of the injector, the fitting clearance of the intake system, and the fitting clearance of the exhaust system to ensure the service life of the engine and the normal operation of the injector.

▲ When installing the fuel injector on the engine, it is necessary to clean the engine block, cylinder head and other parts connected to the fuel injector, and ensure that there is no dust, carbon deposits, water, rust spots, etc.

▲ Before installing, check whether the fuel injector nozzle gasket has been replaced and installed on the fuel injector.

▲ When installing the fuel injector, apply lubricant between the fuel injector, fuel nozzle sealing gasket and o-ring

▲ Without replacing new gasket can lead to: deformation of the tight cap of nozzle, deformation of nozzle, deformation of nozzle orifice, oil leakage and air leakage, which will cause serious damage to the fuel injector and nozzle to break and cause damage to the engine.

When installing the injector on the engine, please carefully check the components related to the installation of the injector, such as the injector pressure plate, screw, injector rod and other accessories are not deformed, and install it in strict accordance with the operation steps of the engine maintenance manual.

▲ It is forbidden to operate the bare injector for a long time in an environment with serious dust pollution and corrosion to iron products.

A It is forbidden to operate the bare injector for a long time in a strong magnetic field environment.

2.4.0445120332 Injector's Reasons for Not Working Normally

- (1) There is air in the oil circuit of the engine fuel system.
- (2) Vehicle oil pump oil supply system is not normal.
- (3) Engine common rail system oil leakage or pressure limiting valve damage.
- (4) There is a short circuit, cutting out and poor contact in the wiring harness connected to the fuel injector of the vehicle.
- (5) The long-term placement of the injector causes the anti-rust oil to solidify, and the internal components are stuck or the oil holes are blocked.
- A Before installing, carefully check whether other components in the common rail system except the fuel injector is damaged so as to prevent the fuel injector from not working properly after being replaced.

2.5.0445120332 Injector's Causes of Damage

(1) Didn't operate properly according to engine maintenance manual during disassembly or installation,

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133 Email : ruby@shumatt.comWebsite : www.shumatt.com



resulting in damage to the injector.

- (2) The fuel oil used for the vehicle does not meet the standard cause damage to the injector, such as: the water content in the fuel oil exceeds the standard, iron powder, aluminum powder, sulfide impurities exceed the standard, etc.
- (3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating oil of the engine system for a long time will cause abnormal wear of the engine, excessive exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced during maintenance or the replaced filter cannot reach the original filter standard. all above reasons can cause damage to the injector.
- (4) The abrasion of the oil pump produces iron powder and aluminum powder enter the fuel injector and cause damage to the fuel injector.
- (5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the fuel injector and causing damage to the fuel injector.
- (6) The fuel injector is damaged due to replacement or adjustment of the relevant parts of the fuel injector. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the injector fails to meet the original standard.
- (7) The engine is overheated and overloaded for a long time working results in damage to the fuel injector.
- (8) The injector will be damaged naturally at the end of its working life.
- (9) The injector is magnetized (injector parts' magnetic exceeded) causing the injector to not work properly.
- ▲ Before replacing the fuel injector, please check the engine parts carefully according to the engine maintenance manual to avoid the fuel injector being damaged again after replacement.

2.6.0445120332 Injector's Technical Support Obtaining Methods

(1) (1) Injector Technical File, visit http://shumatt.com to get the technical file.

(2) Injector Technical Videos

Facebook: Visit https://www.facebook.com/hison.li to get the technical videos, constantly follow can get more information.

YouTube: https://www.youtube.com/channel/UCByvYBx7VjV mAfxh Hu-aw to get the technical videos, constantly follow can get more information.

Shumatt: Visit http://shumatt.com to get the technical videos.

3.0445120332 Injector's Purchase and Delivery

3.1.0445120332 Injector's Purchase Payment Terms

Payment Terms: T/T, PayPal, Alipay, WeChat

Please contact our salesmen for specific payment information.

3.2.0445120332 Injector's Main Sales Markets

Injector main sales markets: Asia, Europe, North America, South America, Africa etc.

3.3.0445120332 Injector's Declaration Requirements

Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133 Email :ruby@shumatt.comWebsite : www.shumatt.com



3.4.0445120332 Injector's Shipping Ways

Destination in China areas: SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

Destinations out of China's areas: DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

3.5.0445120332 Injector's Lead time

Lead time: Send out within 3 – 7 working days after receiving payment (Except for special products and special cases)

3.6.0445120332 Injector's Logistics Time for Destination Out of China's Areas

DHL Logistics Time:

Country or Region of Departure	Hong Kong, China	Other Countries or Regions of Asia	Australia and New Zealand	Europe	America	Other Countries
China's Mainland	7 Days	7 Days	8 Days	8 Days	8-12 Days	7-10 Days

UPS Logistics Time: Country or Region of Departure: China's Mainland

Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time
Japan	3 Days	THE PERSON NAMED IN COLUMN	5-7 Days	Egypt	5-7 Days
Turkey	5-7 Days	Singapore	3 Days	Switzerland	5-7 Days
Bahrain	5-7 Days	Latvia	7-10 Days	New Zealand	7-10 Days
Sri Lanka	5-7 Days	Thailand	3 Days	Austria	5-7 Days
Romania	5-7 Days	Vietnam	3-5 Days	Estonia	5-7 Days
Malaysia	3-5 Days	Israel	5-7 Days	Mexico	7-10 Days
France	5-7 Days	America	5-7 Days	United Arab Emirates	5-7 Days
Italy	5-7 Days	Netherlands	5-7 Days	Bengal	7-10 Days
Lebanon	5-7 Days	Philippine	3-5 Days	Greece	7-10 Days
South Korea	3 Days	Spain	5-7 Days	Myanmar	5-7 Days
Canada	5-7 Days	Germany	5-7 Days	Saudi Arabia	7-10 Days
Portugal	5-7 Days	Australia	5-7 Days	South Africa	7-10 Days
Denmark	5-7 Days	Belgium	5-7 Days	Ukraine	7-10 Days
India	7-10 Days	Qatar	7-10 Days	Poland	5-7 Days
Indonesia	3-5 Days	Morocco	7-10 Days	Pakistan	7-10 Days
Kuwait	7-10 Days	7-1	Man Jean	301 301	701

The logistics time is for reference only , subjects are according to the actual arrival.

3.7.0445120332 Injector's Packing

Domestic express packaging: Usually wrapped in waterproof scotch tape, such as picture No.2.

International express packaging: Wrapped with waterproof yellow tape After wrapping the black protective film, such as picture No. 3.

Pallet Shipping: Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 4, Also, the products can be packaged according to customers' requirements.

▲ The packing tray is made of plastic and can be recycled.

▲ Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are non degradable materials, please dispose of them properly.

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133 Email : ruby@shumatt.com Website : www.shumatt.com




▲ Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury.



Pic No. 2

Domestic express packaging:

Wrapped by Transparent tape
black protective film



Pic No. 3

International express packaging:

Wrapped with yellow tape after wrapping



Pic No. 4

Pallet Shipping: Use pallet that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties

4.0445120332 Injector's Storage Standard

(1) Choose a suitable storage place

The warehouse and cargo yard where the fuel injector is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acids, alkalis, salts and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir area dry.

(2) Strict requirements of warehousing

Strict inspections should be carried out when the fuel injectors are put into storage, the surface cleaning work should be done well to remove water traces, oil stains, ash and other dirt, remove the rust and do anti-rust treatment in time. Packaged injectors must be protected from damage.

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133 Email : ruby@shumatt.com Website : www.shumatt.com

(3) Keep the warehouse dry and preventing moisture

The relative humidity is usually below 70% for the fuel injectors placed in the room, and the corrosion of the fuel injectors is significantly reduced.

Injectors must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

(4) Stack Properly


After the injector is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse

If the fuel injector package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and oil applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied oil in time.

- ▲ It is forbidden to leave the injector exposed in the air for a long time.
 - ▲ It is forbidden to store acids, alkalis, salts and other substances together with the injector.
 - ▲ The unpacked fuel injector must be rust-proof during secondary storage.

5. Company Information Office Locations Global **Exhibitions** 5.1 Company Introduction Chinese Name: 深圳市舒马特科技有限公司 English Name: Shenzhen Shumatt Technology Co., Ltd **☐ Mob Phone/WeChat**: +86-13410541523 ☐ **HK Telephone:** +852-67653519 Telephone: +86-755-23215133

 $\label{lem:mob_whatsapp: +86 13410541523 Tel: +8675523215133} \\ Email: \underline{ruby@shumatt.com} \\ Website: \underline{www.shumatt.com} \\$





Email: ruby@shumatt.com

Website: www.shumatt.net

Shenzhen Office: 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

Shenzhen Office: Room 428-430, Building B, Huafeng Zhigu Technology Industrial Park, Exit B, Fuyong Metro Station, Bao'an District, Shenzhen, China's Mainland

Hong Kong Office: Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

After-sales Service Address: Please contact our salesmen to obtain and provide the corresponding product maintenance reasons (Reference: 1.8.0445120332 Injector Warranty Instructions)

5.2. Sales-men's Contact Information

No.	Name	WeChat/ WhatsApp	Email	(f)	You Tube
1	Ruby	+86-13410541523	ruby@shumatt.com	Hison Li	Hison Li
2	lvy	+86-18025309821	sales@shumatt.com	Ivy Shumatt	Shumatt IVY
3S ⁸	Rebecca	+86-18025349821	sales01@shumatt.com	Rebecca SHUMATT	SHUMATT Rebecca
4	Janny	+86-18028749821	sales02@shumatt.com	Janny shumatt	Janny Shumatt
5	Sam	+86-13316859821	Sales8@shumatt.com	Shumatt Sam	Sam Shumatt
6	Natalie	+86- 18938945856	sales15@shumatt.com	Shumatt Natalie	Lin Natalie
7	Ada	+86-1342286332	sales5@shumatt.com	Shumatt Ada	Ada Shumatt
8	Hison Li	+86-18318811871	web@shumatt.com	Hison Li	Hison Li
9	Mecca	+86-18938948618	sales11@shumatt.com	Shumatt Mecca	Shumatt Mecca
10	య్ Eric యో	+86 18319033328	sales3@shumatt.com		Party Control of
11	Wayne (Joaquín enespañol)	+86-13316959821	wayne@shumatt.com	shumattway ne	Wayne Shumatt
12	Sylvia	+86 18312499884	sales6@shumatt.com	100 miles	
Visit http://shumatt.com to obtain the latest information of salesmen					
PS: Shumatt's sales-men's emails are all end with @shumatt.com					

6. Copyright Statement

The copyright of any contents (including but not limited to parameters, data, text, charts, images, sounds or videos, etc.) provided in "0445120332 Injector CRIN3-18 Technical File" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "0445120332 Injector CRIN3-18 Technical File" in any way. At the same time, any conditions to spread, re-post, display the contents of "0445120332 Injector CRIN3-18 Technical File" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "0445120219 Injector CRIN3-18 Technical File" will violate the "Copyright Law of the People's Republic of China" and other laws and regulations and the provisions of relevant international conventions.

Mob/Whatsapp: +86 13410541523 Tel: +8675523215133 Email: ruby@shumatt.comWebsite: www.shumatt.com